

INDUSTRIAL COMPONENT DATA

XVTL-D-12-18-R 114647 EATON ELECTRIC Door, right, for HxW 1800x1200mm

Brand: EATON - MOELLER | Manufacturer Part Number: XVTL-D-12-18-R



Manufacturer	EATON - MOELLER
MPN / Reference	XVTL-D-12-18-R
Catalog number	114647
Category	Door/operating panel (switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-B7341B28F4
Generated	2026-08-05

Product Overview

Door, right, for HxW=1800x1200mm

Door with hinges and locking swinghandle, sheet steel, powder-spray painted RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

Fuse-link, LV, 12 A, AC 600 V, 10 x 38 mm, 13/32 x 1-1/2 inch, CC, UL, time-delay, rejection-type Fuse, fuse-link, low voltage, 12 A, AC 600 V, 10 x 38 mm, 13/32 x 1-1/2 inch, Class CC, UL, time-delay, cylindrical, rejection-type, branch circuit. Breaking capacity 200 kA [Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 12 A Rated voltage AC 600 V Size 10 x 38 mm

13/32 x 1-1/2 inch Utilization category CC Description rejection-type Breaking Capacity 200 kA usable for size/applications branch circuit Release characteristic [class] time-delay Standard/Approval UL Shape cylindrical , Technical data ETIM 7.0 Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) ( [AFZ797013]) Size 10x38 mm Rated voltage 600 - 600 V Rated voltage Other Voltage type AC Utilization category Other Rated operating frequency 45 - 62 Hz Nominal current 12 A With striker No Release characteristic CC Breaking capacity 200 kA]

ETIM for 114647 Cabinets and enclosures (EC000747)

Feature Name

Feature Value

Model (EF000010)

Stop door

Version as glazed door (EF006966)

No

Version as door for disconnecting switch interlocking (EF006967)

No

Width (EF000008)

592.7 mm

Height (EF000040)

40 mm

Depth (EF000049)

1740 mm

EMC-version (EF001062)

Yes

Material (EF002169)

Steel

Colo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XVTL-D-12-18-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.