

INDUSTRIAL COMPONENT DATA

XVTL-D-10-20-R 114652 EATON ELECTRIC Door, right, for HxW 2000x1000mm

Brand: EATON - MOELLER | Manufacturer Part Number: XVTL-D-10-20-R



Manufacturer	EATON - MOELLER
MPN / Reference	XVTL-D-10-20-R
Catalog number	114652
Category	Door/operating panel (switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-6C477827D8
Generated	2026-08-06

Product Overview

Door, right, for HxW=2000x1000mm

Door with hinges and locking swinghandle, sheet steel, powder-spray painted RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

Fuse-link, LV, 20 A, AC 250 V, 14 x 51 mm, RK5, UL, time-delay, dual-element Fuse, fuse-link, low voltage, 20 A, AC 250 V, 14 x 51 mm, Class RK5, UL, time-delay, dual-element, motor overload protection, ground fault protection, short-circuit protection, CE, UL Listed, Standard 248-12, Class RK-5, Guide JDDZ, File E4273, CSA Certified, C22.2 No. 248.12, Class 1422-02, File 53787, time-delay 8 seconds (minimum) at 500% of rated current [Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 20 A Rated voltage AC 250 V Size 14 x 51 mm Utilization category RK5 Description dual-element usable for size/applications motor overload protection ground fault protection

short-circuit protection Release characteristic [class] time-delay Standard/Approval UL Standards/Regulations CE UL Listed, Standard 248-12

Class RK-5, Guide JDDZ, File E4273

CSA Certified, C22.2 No. 248.12, Class 1422-02, File 53787 Time delay time-delay 8 seconds (minimum) at 500% of rated current , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015]) Construction size Other Rated current 20 A Rated voltage 250 V Voltage type AC/DC Rated switching capacity 200 kA Utilization category Other Type of fuse status indicator None Insulated metal gripping I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XVTL-D-10-20-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.