

INDUSTRIAL COMPONENT DATA

BPZ-TP-12 119219 EATON ELECTRIC Door support bar for H 1150mm

Brand: EATON - MOELLER | Manufacturer Part Number: BPZ-TP-12



Manufacturer	EATON - MOELLER
MPN / Reference	BPZ-TP-12
Catalog number	119219
Category	Accessories/spare parts for small distribution board
Minimum order	1 Pcs
Document ID	EO-1144C1DE93
Generated	2026-08-04

Product Overview

Door support bar for H=1150mm

Service distribution system-Profi Plus (floor standing distribution board, wall-mounting/flush-mounted distribution board)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Fuse-link, low voltage, 12 A, AC 600 V, DC 170 V, 33.3 x 10.4 mm, G, UL, CSA, time-delay Fuse, Fuse-link, low voltage, 12 A, AC 600 V, DC 170 V, 33.3 x 10.4 mm, G, UL, CSA, time-delay, cylindrical, size-rejecting, fusible branch panelboards, HVAC branch circuit protection, UL 248-5, Breaking Capacity 100 kA, time-delay 12 seconds (minimum) at 200% of rated current [Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 12 A Rated voltage AC 600 V DC 170 V Size 33.3 x 10.4 mm Utilization category G Description size-rejecting Breaking Capacity 100 kA usable for size/applications fusible branch panelboards, HVAC branch circuit protection Release characteristic [class] time-delay Standard/Approval UL

CSA Shape cylindrical Standards/Regulations UL 248-5 Time delay time-delay 12 seconds (minimum) at 200% of rated current , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) ()

[AFZ797013]) Size Other Rated voltage 600 - 600 V Rated voltage Other Voltage type AC/DC Utilization category Other Rated operating frequency 45 - 62 Hz Nominal current 12 A With striker No Release characteristic G Breaking capacity 100

kA]

ETIM for 119219 Distribution boards (EC002287)

Feature Name

Feature Value

Type of accessory/spare part (EF00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPZ-TP-12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.