

INDUSTRIAL COMPONENT DATA

M22S-DDL-GR 216699 Y7-216699 EATON ELECTRIC Double actuator pushbutton, +indicator light, green/white/red

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-DDL-GR



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-DDL-GR
Catalog number	Y7-216699
Category	Front element for push button
Minimum order	5 Pcs
Document ID	EO-289B7EAE50
Generated	2026-08-02

Product Overview

Double actuator pushbutton, +indicator light, green/white/red

M22S-DDL-GR

Eaton Moeller® series M22 Double actuator pushbutton, RMQ-Titan, Actuators and indicator lights non-flush, momentary, White lens, green, red, Blank, Bezel: black

Double actuator pushbutton, Product range: RMQ-Titan, Single unit, Design: Actuators and indicator lights non-flush, momentary, Description: White lens, button plate: green, red, Button plate Blank, Degree of Protection: IP66, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7 x 54,7, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Double actuator pushbutton Catalog Number 216699 Model Code

M22S-DDL-GR EAN 4015082166991 Product Length/Depth 30 mm Product Height 55 mm Product Width 30 mm Product Weight 0.015 kg Compliances GoST-R

CE Marked

Bureau Veritas Certifications CCC Marked

CSA Certified

Lloyd's Register Certified

CE

IEC/EN 60947

UL 508

UL Category Control No.: NKCR

CSA

VDE 0660

CSA-C22.2 No. 94-91

UL File No.: E29184

CSA File No.: 012528

IEC/EN 60947-5

UL

CSA Class No.: 3211-03

CSA-C22.2 No. 14-05

DNV

GL

LR Catalog Notes Includes contact block mounting adapter. Features & Functions

Bezel color Black Bezel material Plastic Design Non-Flush

Classical Fitted with: Front ring Illumination Illuminated Inscription Blank Lens color White General

Degree of protection NEMA 4X

NEMA 13

IP66

NEMA 3R

NEMA 12 Degree of protection (front side) NEMA 4X

IP66 Lifespan, mechanical 200,000 Operations Opening diameter 22.5 mm Operating frequency 3600 Operations/h Product category RMQ-Titan Size Front dimensions: 29,7 x 54,7 mm Suitable for Illumination Type Double actuator Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-DDL-GR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.