

INDUSTRIAL COMPONENT DATA

M22S-DDL-WS-X1/X0 216707 Y7-216707 EATON ELECTRIC

Double actuator pushbutton, +indicator light, white I/whit..

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-DDL-WS-X1/X0



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-DDL-WS-X1/X0
Catalog number	Y7-216707
Category	Front element for push button
Minimum order	5 Pcs
Document ID	EO-B060193741
Generated	2026-08-05

Product Overview

Double actuator pushbutton, +indicator light, white I/white/black 0

M22S-DDL-WS-X1/X0

Eaton Moeller® series M22 Double actuator pushbutton, RMQ-Titan, Actuators and indicator lights non-flush, momentary, White lens, white, black, inscribed, Bezel: black

Double actuator pushbutton, Product range: RMQ-Titan, Single unit, Design: Actuators and indicator lights non-flush, momentary, Description: White lens, button plate: white, black, Button plate inscribed, Degree of Protection: IP66, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7 x 54,7, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Double actuator pushbutton Catalog Number 216707 Model Code

M22S-DDL-WS-X1/X0 EAN 4015082167073 Product Length/Depth 30 mm Product Height 55 mm Product Width 30 mm

Product Weight 0.015 kg Certifications CE

CSA-C22.2 No. 14-05

IEC/EN 60947-5

UL File No.: E29184

CSA Class No.: 3211-03

CSA

IEC/EN 60947

CSA File No.: 012528

UL Category Control No.: NKCR

CSA-C22.2 No. 94-91

UL 508

VDE 0660

UL

DNV

GL

LR Features & Functions

Bezel color Black Bezel material Plastic Design Non-Flush

Classical Features Labelled Fitted with: Front ring Inscription Inscribed Lens color White General

Degree of protection IP66

NEMA 12

NEMA 13

NEMA 4X

NEMA 3R Degree of protection (front side) IP66

NEMA 4X Lifespan, mechanical 200,000 Operations Opening diameter 22.5 mm Operating frequency 3600 Operations/h

Product category RMQ-Titan Size Front dimensions: 29,7 x 54,7 mm Suitable for Illumination Type Double actuator Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min

40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Communication

Connection to SmartWire-DT With SWD-R...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-DDL-WS-X1/X0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.