

INDUSTRIAL COMPONENT DATA

M22-DDL-WS 216704 Y7-216704 EATON ELECTRIC Double actuator pushbutton, +indicator light, white/white/black

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DDL-WS



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DDL-WS
Catalog number	Y7-216704
Category	Front element for push button
Minimum order	5 Pcs
Document ID	EO-EB7171B50C
Generated	2026-08-02

Product Overview

Double actuator pushbutton, +indicator light, white/white/black

M22-DDL-WS

Eaton Moeller® series M22 Double actuator pushbutton, RMQ-Titan, Actuators and indicator lights non-flush, momentary, White lens, white, black, Blank, Bezel: titanium

Double actuator pushbutton, Product range: RMQ-Titan, Single unit, Design: Actuators and indicator lights non-flush, momentary, Description: White lens, button plate: white, black, Button plate Blank, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7 x 54,7, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Double actuator pushbutton Catalog Number 216704 Model Code M22-DDL-WS
EAN 4015082167042 Product Length/Depth 30 mm Product Height 55 mm Product Width 30 mm Product Weight 0.015 kg
Compliances CE Marked Certifications CSA Std. C22.2 No. 94-91

UL 508

IEC 60947-5

CSA Std. C22.2 No. 14-05

EN 60947-5

VDE

CSA

CSA Class No.: 3211-03

CSA-C22.2 No. 14-05

UL Category Control No.: NKCR

IEC/EN 60947-5

CSA File No.: 012528

UL

IEC/EN 60947

UL File No.: E29184

CSA-C22.2 No. 94-91

VDE 0660

CE

DNV

GL

LR Features & Functions

Bezel color Titanium Bezel material Plastic Design Non-Flush

Classical Fitted with: Front ring Inscription Blank Lens color White General

Degree of protection NEMA 12

NEMA 3R

NEMA 13

IP66

NEMA 4X Degree of protection (front side) IP66

NEMA 4X Lifespan, mechanical 200,000 Operations Opening diameter 22.5 mm Operating frequency 3600 Operations/h

Product category RMQ-Titan Size Front dimensions: 29,7 x 54,7 mm Suitable for Illumination Type Double actuator Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, const...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DDL-WS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.