

INDUSTRIAL COMPONENT DATA

DMV-630N/1+SH 1814449 Y8-1814449 EATON ELECTRIC Industrial Automation Bussines and Industrial Control Device..

Brand: EATON - MOELLER | Manufacturer Part Number: DMV-630N/1+SH



Manufacturer	EATON - MOELLER
MPN / Reference	DMV-630N/1+SH
Catalog number	Y8-1814449
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-CEE5EBD2A8
Generated	2026-08-03

Product Overview

Industrial Automation Bussines and Industrial Control Devices Switching Devices

DMV-630N/1+SH

Switch-disconnector, 3p+N, 630A, with shaft and handle

Switch-disconnector Dumeco part no. DMV 630N/1, switching duty 630 A, 3 pole + N (fixed), with shaft and rotary handle part no. C with switch position indication I/O, height of switch: 182mm (from bottom of switch to top of operating shaft/rotary handle), including connection materials

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

Switch-disconnector, 3p+N, 630A, with shaft and handleSwitch-disconnector Dumeco part no. DMV 630N/1, switching duty 630 A, 3 pole + N (fixed), with shaft and rotary handle part no. C with switch position indication I/O, height of switch: 182mm (from bottom of switch to top of operating shaft/rotary handle), including connection materialsDelivery program

Product rangeSwitch-disconnector

Main switch

maintenance switchPart group referenceDMVStop Functionoptionalwith operating shaft and knobNotesvisible

contactsInformation about equipment suppliedauxiliary contact fitted by user.

including connection materialsNumber of poles3P + N (solid)Auxiliary contacts0 N/O0 N/CDegree of ProtectionIP00

IP20 with terminal coverDesignsurface mountingContact sequenceMotor rating AC-23A, 50 - 60 Hz [P]400 V [P]375
kWRated uninterrupted current [Iu]630 ANote on rated uninterrupted current IuRated uninterrupted current Iuis specified for
max. cross-section.Technical data
GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204
Switch-disconnector according to IEC/EN 60947-3CertificationsCE, RoHs, KEMA, EAC, LloydsAmbient
temperatureOperation [?]-25 - +55 °CAmbient temperatureStorage [?]-30 - +80 °COvervoltage category/pollution
degreeIII/3Rated impulse withstand voltage [Uimp]12 kVRated insulation voltage [Ui]1000 VMounting positionAs
requiredContactsMechanical variablesNumber of poles3P + N (solid)Mechanical variablesAuxiliary contacts0
N/OMechanical variablesAuxiliary contacts0 N/CElectrical charac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DMV-630N/1+SH with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.