

INDUSTRIAL COMPONENT DATA

DX-EMC34-250-L 174614 Y7-174614 EATON ELECTRIC EMC filter for Frequency Converter three-Phase 520V 250A

Brand: EATON - MOELLER | Manufacturer Part Number: DX-EMC34-250-L



Manufacturer	EATON - MOELLER
MPN / Reference	DX-EMC34-250-L
Catalog number	Y7-174614
Category	Accessories/spare parts for frequency controller
Minimum order	1 Pcs
Document ID	EO-C74341C52D
Generated	2026-08-05

Product Overview

EMC filter for Frequency Converter; three-Phase; 520V; 250A

DX-EMC34-250-L

Radio interference suppression filter, three-phase, low leakage current, ULN= max. 520 + 10% V, 250 A, For use with: DA1, DG1

Radio interference suppression filter, Description: three-phase, low leakage current, Mains voltage (50/60Hz): ULN= max. 520 + 10% V, Rated operational current: Ie= 250 A, For use with: DA1, DG1, Degree of Protection: IP20, Connection type: Screw terminal, PE stud, Weight: m 12,2 kg, Notes: Separate mounting, Standards: EN 50178, IEC 61800-3, EN 61800-3 incl. A11

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Power XL Frequency Converters
--------------	---

Additional Product Information

Radio interference suppression filter, three-phase, low leakage current, ULN= max. 520 + 10% V, 250 A, For use with: DA1, DG1Radio interference suppression filter, Description: three-phase, low leakage current, Mains voltage (50/60Hz): ULN= max. 520 + 10% V, Rated operational current: Ie= 250 A, For use with: DA1, DG1, Degree of Protection: IP20, Connection type: Screw terminal, PE stud, Weight: m 12,2 kg, Notes: Separate mounting, Standards: EN 50178, IEC 61800-3, EN 61800-3 incl. A11

General specificationsProduct nameEaton DX Radio interference suppression filter - lowPart

no.DX-EMC34-250-LEAN4015081710690Product Length/Depth220 millimetreProduct height525 millimetreProduct width155 millimetreProduct weight13.2 kilogramCertificationsCertified by UL for use in Canada

EN 50178

UL 1283

UL File No.: E192040

UL

IEC/EN 61800-3

ULProduct TradenameDXProduct TypeAccessoryProduct Sub TypeRadio interference suppression filter - lowCatalog

Noteslow leakage currentFeatures & FunctionsNumber of phases3General informationAccessory/spare part

typeFilterDegree of protectionIP20Product CategoryAccessoriesUsed withDA1

DG2Climatic environmental conditionsAltitudeMax. 2000 m

At higher altitudes observe deratingAmbient operating temperature - max50 °CAmbient operating temperature - min-25

°CConnectionConnection typeScrew terminal, PE studElectrical ratingRated operational current (Ie) - max250 ADesign

verificationHeat dissipation capacity Pdiss0 WRated operational current for specified heat dis...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DX-EMC34-250-L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.