

INDUSTRIAL COMPONENT DATA

DX-SIN3-065-A 184496 EATON ELECTRIC Sine filter, three-phase, 500 V + 0% (50/60 Hz) V AC, 65 A, For use with..

Brand: EATON - MOELLER | Manufacturer Part Number: DX-SIN3-065-A



Manufacturer	EATON - MOELLER
MPN / Reference	DX-SIN3-065-A
Catalog number	Y7-184496
Category	Accessories/spare parts for frequency controller
Minimum order	1 Pcs
Document ID	EO-99707D1565
Generated	2026-08-05

Product Overview

Sine filter, three-phase, 500 V + 0% (50/60 Hz) V AC, 65 A, For use with: DA1, DG1

Sine filter, Description: three-phase, For use with: DA1, DG1, Max. permissible connection voltage: 500 V + 0% (50/60 Hz) V AC, Rated operational current: I_e = 62 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Power XL Frequency Converters
--------------	---

Additional Product Information

Sine filter, three-phase, 500 V + 0% (50/60 Hz) V AC, 65 A, For use with: DA1, DG1
Sine filter, Description: three-phase, For use with: DA1, DG1, Max. permissible connection voltage: 500 V + 0% (50/60 Hz) V AC, Rated operational current: I_e = 65 A
Delivery program

Product rangeAccessoriesAccessoriesSine filterDescriptionthree-phaseFor use withDA1, DG1Max. permissible connection voltage500 V + 0% (5 - 150 Hz) V ACRated operational current [I_e]65 AInductance [L]0.75 mHInstructionsDifferential-mode inductance, common-mode inductance: 1.4 mHMaximum heat dissipation [P_v]650 WTechnical data

GeneralStandardsIEC/EN 61558 Part 1 +AA + AC, IEC/EN 61588 Part 20Operating temperature-10 - +45 °CStorage [?] -25 - +85 °CAltitude0 - 1000 a.s.l., up to 4000 with current reduction (see IL) mMounting positionStanding vertically, suspended horizontallyFree surrounding areas> 100 MMDegree of ProtectionIP00Rated duty factor100 % DFElectrical dataRated operational voltage3 AC 230 V

3 AC 400 VMax. permissible connection voltage500 V + 0% (5 - 150 Hz) V ACRated frequency [f]0 - 120 HzInsulation classHRated operational current [I_e]65 AInductance [L]0.75 mHMaximum heat dissipation [P_v]650 WVoltage sag [U_k]6.5 %ConnectionTerminations?PE stud?Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [In]65 A Equipment heat dissipation, current-dependent [Pvid]650 W Static heat dissipation, non-current-dependent [Pvs]0 W Heat dissipati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DX-SIN3-065-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.