

INDUSTRIAL COMPONENT DATA

E52Q-DL25UAD01 135808 Y7-135808 EATON ELECTRIC

Proximity switch, inductive, 1N/O+1N/C, Sn 25mm, 4L, 10-48VDC..

Brand: EATON - MOELLER | Manufacturer Part Number: E52Q-DL25UAD01



Manufacturer	EATON - MOELLER
MPN / Reference	E52Q-DL25UAD01
Catalog number	Y7-135808
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-98D807AFF9
Generated	2026-08-01

Product Overview

Proximity switch, inductive, 1N/O+1N/C, Sn=25mm, 4L, 10-48VDC, NPN, PNP, quad.40, insulated material
E52Q-DL25UAD01

Eaton Moeller® series E52 Proximity switch, inductive, 1N/O+1N/C, Sn=25mm, 4L, 10-48VDC, NPN, PNP, quad.40, insulated material

Proximity switch, Inductive Sensors, Product range: E52 Cube Series, Description: Housing adapter, Connection: 4-wire, Design (outer dimensions): 40 x 40 x 40 mm, Rated operational voltage: $U_e = 10 - 48 \text{ V DC}$, Rated switching distance: $S_n = 25 \text{ mm}$, Type of mounting: Non-flush, Switching type: NPN, PNP, Plug-in connection M12 x 1, Contacts N/C = Normally closed: 1 NC, Contacts N/O = Normally open: 1 N/O, Material: Zinc/Insulated material, Degree of Protection: IP67, Standards: IEC/EN 60947-5-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Sensors
--------------	---------------------------

Additional Product Information

General specifications

Product Name Eaton E52 inductive proximity sensor Catalog Number 135808 Model Code E52Q-DL25UAD01 EAN 4015081326013 Product Length/Depth 41.28 mm Product Height 79.38 mm Product Width 44.45 mm Product Weight 0.27 kg Certifications Certified by UL for use in Canada
CSA-C22.2 No. 14

UL File No.: E166051

CE

CSA File No.: UL report applies to both US and Canada

UL Category Control No.: NRKH, NRKH7

UL

UL 508

IEC/EN 60947-5-2 Catalog Notes Housing adapter Product specifications

Type Inductive sensor Electric connection type Connector M12 Enclosure material finishing Other Surface finishing Zinc alloy Actuation type Metallic Target Enclosure material Plastic Enclosure type Cuboid Category (EN 954-1) B Explosion safety category for dust None Explosion safety category for gas None Safety performance level (EN ISO 13849-1) None SIL (IEC 61508) None Ambient operating temperature - max 70 °C Ambient operating temperature - min -40 °C Diameter sensor 0 mm Number of contact energized outputs with signalling function 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Number of outputs (protected contact energized) 0 Number of outputs (protected semiconductor) 0 Number of outputs (semiconductor with signaling function) 1 Operational current (Ib) in the switched state at 24 V DC 25 A Output current at protected output - max 0 mA Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Functions Protection against wire breaka...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E52Q-DL25UAD01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.