

INDUSTRIAL COMPONENT DATA

E57P-18UPN8-Q 197802 Y7-197802 EATON ELECTRIC

Proximity switch, E57P Performance Serie, 1 N/O, 3-wire, 10 -

..

Brand: EATON - MOELLER | Manufacturer Part Number: E57P-18UPN8-Q



Manufacturer	EATON - MOELLER
MPN / Reference	E57P-18UPN8-Q
Catalog number	Y7-197802
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-EFF60EBF71
Generated	2026-08-04

Product Overview

Proximity switch, E57P Performance Serie, 1 N/O, 3-wire, 10 - 48 V DC, M18 x 1 mm, Sn= 8 mm, Non-flush, PNP, Stainless steel, Plug-in connection M12 x 1

E57P-18UPN8-Q

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Sensors
--------------	---------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series E57P Proximity switch Catalog Number 197802 Model Code E57P-18UPN8-Q EAN 4015081949090 Product Length/Depth 69.2 mm Product Height 18 mm Product Width 18 mm Product Weight 0.05 kg

Certifications UL Category Control No.: NRKH, NRKH7

UL File No.: E166051

CSA-C22.2 No. 14

IEC/EN 60947-5-2

UL Listed

Certified by UL for use in Canada

UL 508 Product specifications

Type Inductive sensor Electric connection type Connector M12 Enclosure material finishing Other Actuation type Metallic

Target Enclosure material Metal Enclosure type Cylinder, screw-thread Category (EN 954-1) B Explosion safety category for dust None Explosion safety category for gas None Safety performance level (EN ISO 13849-1) None SIL (IEC 61508) None Ambient operating temperature - max 70 °C Ambient operating temperature - min -40 °C Diameter sensor 18 mm Number of contact energized outputs with signalling function 0 Number of contacts (normally open contacts) 1 Number of outputs (protected contact energized) 0 Number of outputs (protected semiconductor) 0 Number of outputs (semiconductor with signaling function) 1 Operational current (Ib) in the switched state at 24 V DC 10 A Output current at protected output - max 0 mA Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Functions Short-circuit protection Voltage type DC Mounting method Non-flush mounting Material Stainless steel Connection type 3-wire Plug-in connection M12 x 1 Installation type Not....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E57P-18UPN8-Q with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.