

## INDUSTRIAL COMPONENT DATA

# E59-A30C125C02-CV 166687 Y7-166687 EATON ELECTRIC Proximity switch Inductive M30 Analog Sn 1-25mm, 15 30 V D..

Brand: EATON - MOELLER | Manufacturer Part Number: E59-A30C125C02-CV



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | EATON - MOELLER            |
| MPN / Reference | E59-A30C125C02-CV          |
| Catalog number  | Y7-166687                  |
| Category        | Inductive proximity switch |
| Minimum order   | 1 Pcs                      |
| Document ID     | EO-EEF24C5884              |
| Generated       | 2026-08-04                 |

## Product Overview

Proximity switch Inductive; M30; Analog; Sn=1-25mm, 15 - 30 V DC; 0 - 20mA; 0 - 10V; Cable 2m

E59-A30C125C02-CV

Eaton Moeller® series E59 Proximity Sensor, M30, analog, Sn=1-25mm, 15-30VDC, 0-20mA, 0-10V, line 2m Proximity Sensor, Inductive Sensors, Product range: E59 AccuProx Series, Description: Current output (0 - 20 mA) and voltage output (0 - 10 V), Connection: 3-wire/4-wire, Design (outer dimensions): M30 x 1.5 mm, Rated operational voltage: Ue= 15 - 30 V DC, Rated switching distance: Sn= 1 - 25 mm, Type of mounting: Non-flush, Switching type: Analog, 2 m connection cable, Material: Stainless steel, Degree of Protection: IP67, Standards: IEC/EN 60947-5-2

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                           |
|--------------|---------------------------|
| Catalog path | EATON - MOELLER > Sensors |
|--------------|---------------------------|

## Additional Product Information

### General specifications

Product Name Eaton E59 AccuProx analog inductive proximity sensor Catalog Number 166687 Model Code E59-A30C125C02-CV EAN 4015081643455 Product Length/Depth 152.4 mm Product Height 44.45 mm Product Width 127 mm Product Weight 0.45 kg Certifications UL  
UL 508  
CE  
CSA Class No.: 3211-03  
IEC/EN 60947-5-2  
UL Category Control No.: NRKH, NRKH7

UL File No.: E166051

CSA File No.: 50513

CSA

CSA-C22.2 No. 14 Product specifications

Type Inductive sensor Electric connection type Cable Enclosure material finishing Other Actuation type Metallic Target Enclosure material Metal Enclosure type Cylinder, screw-thread Category (EN 954-1) B Explosion safety category for dust None Output voltage 0 - 10 V Explosion safety category for gas None Safety performance level (EN ISO 13849-1) None SIL (IEC 61508) None Ambient operating temperature - max 70 °C Ambient operating temperature - min -40 °C Diameter sensor 30 mm Number of contact energized outputs with signalling function 0 Number of outputs (protected contact energized) 0 Number of outputs (protected semiconductor) 0 Number of outputs (semiconductor with signaling function) 0 Output current at protected output - max 20 mA Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Output current 0 - 20 mA Voltage type DC Mounting method Non-flush mounting Material Stainless steel Connection type 2 m connection cable

3-wire/4-wire Installation type Not flat Degree of protection IP67

NEMA 4X, 6, 13 Interface type None LED indi...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E59-A30C125C02-CV with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.