

INDUSTRIAL COMPONENT DATA

E65-SMPP100-HLD 135713 Y7-135713 EATON ELECTRIC

Diffuse reflective sensor, Sn 100mm, 4L, 10-30VDC, light, NP..

Brand: EATON - MOELLER | Manufacturer Part Number: E65-SMPP100-HLD



Manufacturer	EATON - MOELLER
MPN / Reference	E65-SMPP100-HLD
Catalog number	Y7-135713
Category	Light scanner with background masking
Minimum order	1 Pcs
Document ID	EO-36EA73B623
Generated	2026-08-05

Product Overview

Diffuse reflective sensor, Sn=100mm, 4L, 10-30VDC, light, NPN, PNP, quad 40, insulated material, M12

E65-SMPP100-HLD

Eaton Moeller® series E65 Diffuse reflective sensor, Sn=100mm, 4L, 10-30VDC, light, NPN, PNP, quad 40, insulated material, M12

E65-SM series, product features: bright indicators for voltage, output and TargetLock™, targetLock™ simplifies setup and ensures a high operational reliability. Perfect Prox® models detect targets with different colors at the same range while ignoring background objects. DC models have access to

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Sensors

Additional Product Information

General specifications

Product Name Eaton Moeller® series E65 Diffuse reflective sensor Catalog Number 135713 Model Code

E65-SMPP100-HLD EAN 4015081325061 Product Length/Depth 139.7 mm Product Height 139.7 mm Product Width 38.1 mm Product Weight 0.11 kg Certifications CSA File No.: UL report applies to both US and Canada

IEC/EN 60947-5-2

UL File No.: E166051

UL

Certified by UL for use in Canada

CE

UL 508

CSA-C22.2 No. 14

UL Category Control No.: NRKH, NRKH7 Catalog Notes Yellow Product specifications

Type Optical sensors Electric connection type Connector M12 Fitted with: Background suppression (Perfect Prox)

Enclosure material Plastic Enclosure type Cuboid Operating mode Switching principle: Light switching Explosion safety category for dust None Explosion safety category for gas None Functions Protection against wire breakage

Short-circuit protection

Reflected-light beam

Protection against polarity reversal Voltage type DC Wire size 0 Connection type 4-wire

Plug-in connection M12 x 1 Cable sheath material Other Light type Other Degree of protection NEMA 6

IP68 Interface type Other LED indicator Status indication of Switching state: Red LED

Status indication of Operating voltage: Green LED Switch function type Other Load current Max. 100 mA (Ie) Laser

protection class None Operation agent-safety class Safety class 2 Shock resistance 50 g, Mechanical, Shock duration 10 ms Optical surface material Plastic Output current (mA) - max 100 mA Output current at protected output - m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E65-SMPP100-HLD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.