

INDUSTRIAL COMPONENT DATA

E65-SMSD200-HD 135726 Y7-135726 EATON ELECTRIC

Diffuse reflective sensor, Sn 200mm, 4L, 10-30VDC, dark, NPN,..

Brand: EATON - MOELLER | Manufacturer Part Number: E65-SMSD200-HD



Manufacturer	EATON - MOELLER
MPN / Reference	E65-SMSD200-HD
Catalog number	Y7-135726
Category	Diffuse reflective photoelectric sensor
Minimum order	1 Pcs
Document ID	EO-8C2FE5F8C3
Generated	2026-08-05

Product Overview

Diffuse reflective sensor, Sn=200mm, 4L, 10-30VDC, dark, NPN, PNP, quad 40, insulated material, line 2m
E65-SMSD200-HD

Eaton Moeller® series E65 Diffuse reflective sensor, Sn=200mm, 4L, 10-30VDC, dark, NPN, PNP, quad 40, insulated material, line 2m E65-SMSD200-HD

E65-SM series, product features: bright indicators for voltage, output and TargetLock™, targetLock™ simplifies setup and ensures a high operational reliability. Perfect Prox® models detect targets with different colors at the same range while ignoring background objects. DC models have access to

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Sensors
--------------	---------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series E65 Diffuse reflective sensor Catalog Number 135726 Model Code E65-SMSD200-HD EAN 4015081325191 Product Length/Depth 139.7 mm Product Height 139.7 mm Product Width 38.1 mm Product Weight 0.11 kg Certifications Certified by UL for use in Canada
UL 508
UL
CSA-C22.2 No. 14

IEC/EN 60947-5-2

CE

UL Category Control No.: NRKH, NRKH7

UL File No.: E166051

CSA File No.: UL report applies to both US and Canada Catalog Notes Yellow Product specifications

Type Optical sensors Electric connection type Cable Enclosure material Plastic Enclosure type Cuboid Operating mode

Switching principle: Dark switching Explosion safety category for dust None Explosion safety category for gas None

Functions Reflected-light beam

Protection against polarity reversal

Short-circuit protection

Protection against wire breakage Voltage type DC Wire size 22 Connection type 2 m connection cable

4-wire Cable sheath material Polyvinyl chloride (PVC) Light type Polarity free red light Degree of protection IP68

NEMA 6P, 13 Interface type Other LED indicator Status indication of Switching state: Red LED

Status indication of Operating voltage: Green LED Switch function type Other Load current Max. 100 mA (Ie) Laser

protection class None Operation agent-safety class Safety class 2 Shock resistance 50 g, Mechanical, Shock duration 10

ms Optical surface material Plastic Output current (mA) - max 100 mA Output current at protected output - max 0 mA Rated control su...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E65-SMSD200-HD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.