

INDUSTRIAL COMPONENT DATA

E65-SMTD15-HD 135730 Y7-135730 EATON ELECTRIC

Thru-beam photoelectric sensor, receiver, Sn 15m, 4L, 10-30VDC..

Brand: EATON - MOELLER | Manufacturer Part Number: E65-SMTD15-HD



Manufacturer	EATON - MOELLER
MPN / Reference	E65-SMTD15-HD
Catalog number	Y7-135730
Category	Through beam photoelectric sensor
Minimum order	1 Pcs
Document ID	EO-6BA9EB8279
Generated	2026-08-05

Product Overview

Thru-beam photoelectric sensor, receiver, Sn=15m, 4L, 10-30VDC, dark, NPN, PNP, quad 40, insulated material E65-SMTD15-HD

Eaton Moeller® series E65 Thru-beam photoelectric sensor, receiver, Sn=15m, 4L, 10-30VDC, dark, NPN, PNP, quad 40, insulated material E65-SMTD15-HD

E65-SM series, product features: bright indicators for voltage, output and TargetLock™, targetLock™ simplifies setup and ensures a high operational reliability. Perfect Prox® models detect targets with different colors at the same range while ignoring background objects. DC models have access to

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Sensors

Additional Product Information

General specifications

Product Name Eaton Moeller® series E65 Thru-beam photoelectric sensor Catalog Number 135730 Model Code E65-SMTD15-HD EAN 4015081325238 Product Length/Depth 139.7 mm Product Height 139.7 mm Product Width 38.1 mm Product Weight 0.11 kg Certifications UL Category Control No.: NRKH, NRKH7
Certified by UL for use in Canada
CSA File No.: UL report applies to both US and Canada
UL 508

UL
CSA-C22.2 No. 14
IEC/EN 60947-5-2
CE
UL File No.: E166051 Catalog Notes Yellow Product specifications
Type Optical sensors Device type Receiver Electric connection type Cable Enclosure material Plastic Enclosure type Cuboid Operating mode Switching principle: Dark switching Explosion safety category for dust None Explosion safety category for gas None Functions Short-circuit protection
Protection against wire breakage
Detector (for combination with source)
Protection against polarity reversal
Thru-light beam
For combination with transmitter Voltage type DC Wire size 0 Connection type 2 m connection cable
4-wire Cable sheath material Polyvinyl chloride (PVC) Light type Polarity free red light Degree of protection IP68
NEMA 6 Interface type Other LED indicator Status indication of Operating voltage: Green LED
Status indication of Switching state: Red LED Switch function type Other Load current Max. 100 mA (Ie) Laser protection class None Operation agent-safety class Safety class 2 Shock resistance 50 g, Mechanical, Shock duration 10 ms Optical surface material Plastic Output cu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E65-SMTD15-HD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.