


INDUSTRIAL COMPONENT DATA

E71-SDP-CA 100529 EATON ELECTRIC Proximity switch, optical, long range 35cm, 4L, 10-30VDC, PNP, cable

Brand: EATON - MOELLER | Manufacturer Part Number: E71-SDP-CA



Manufacturer	EATON - MOELLER
MPN / Reference	E71-SDP-CA
Catalog number	100529
Category	Diffuse reflective photoelectric sensor
Minimum order	1 Pcs
Document ID	EO-CAACF59742
Generated	2026-08-05

Product Overview

Proximity switch, optical, long range 35cm, 4L, 10-30VDC, PNP, cable

E71 NanoView series, product features: optical miniature sensor, very minimal size in cube form, IP66_x, status LED for Power und Output, light and dark switching, visible red LED beam enables simple commissioning and adjustment, diffuse Reflective

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Proximity switch, optical, long range 35cm, 4L, 10-30VDC, PNP, cable Eaton Catalog No. E71-SDP-CA E71 NanoView series, product features: optical miniature sensor, very minimal size in cube form, IP66_x, status LED for Power und Output, light and dark switching, visible red LED beam enables simple commissioning and adjustment, diffuse Reflective [Delivery program

Basic function Optical sensors Product range E71 NanoView Series For connection of: 2 m connection cable Design (outer dimensions) Rectangular (20 x 12 x 32) mm Rated operational voltage [Ue] 10 - 30 V DC Rated switching distance [Sn] 350 mm Description Beam: straight Connection 4-wire Function Reflected-light beam Type of light Infra-red Material Insulated material Switching type PNP Switching principle Adjustable bright/dark switching Information relevant for export to North America Product Standards UL 508; CSA-C22.2 No. 14; IEC60947-5-2; CE marking

UL File No. E166051

UL Category Control No. NRKH, NRKH7

CSA File No. UL report applies to both Canada and US

North America Certification UL listed, certified by UL for use in Canada

Max. Voltage Rating 30 V DC

Degree of Protection IEC: IP66; UL/CSA Type: -

, Technical data

General Ambient temperature -25 - +55 Operation [?] -25 - +55 °C Storage [?] -25 - +70 °C Mechanical shock resistance 30

Shock duration 11 ms g Degree of Protection IP66 Vibration Amplitude 0.5 mm: 10 - 55 Hz.

IEC/EN 60068-2-6 Characteristics Rated switching distance Rated switching distance [Sn] 350...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E71-SDP-CA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.