

INDUSTRIAL COMPONENT DATA

E76-CLRMKP-M12 166927 EATON ELECTRIC Detector

Photoelectric color HxWxD 50x25x50mm Sn 5-45mm 10 30 V DC PNP ..

Brand: EATON - MOELLER | Manufacturer Part Number: E76-CLRMKP-M12



Manufacturer	EATON - MOELLER
MPN / Reference	E76-CLRMKP-M12
Catalog number	166927
Category	Luminescence sensor
Minimum order	1 Pcs
Document ID	EO-3B8CE00F5E
Generated	2026-08-06

Product Overview

Detector Photoelectric color; HxWxD=50x25x50mm; Sn=5-45mm; 10 - 30 V DC; PNP; Connector M12

Optical sensors, Reflected-light beam, Color sensing, 3 NO PNP outputs, 8 conductor, 10 - 30 V DC, Sn = 450 mm, Plug-in connection M12 x 1

IntelliView Serie, product features: optical sensor, no entry, programming for the detection of 3 different colors, 5-45 mm sensing range, rectangular plastic housing, integrated display, status LED, two programming buttons

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series E76 Optical color sensor Catalog Number 166927 Model Code E76-CLRMKP-M12
EAN 4015081643035 Product Length/Depth 25 mm Product Height 50 mm Product Width 50 mm Product Weight 0.43 kg

Certifications UL File No.: E166051

UL

CSA File No.: UL report applies to both US and Canada

UL Category Control No.: NRKH, NRKH7

CE

UL 508

IEC/EN 60947-5-2

Certified by UL for use in Canada

CSA-C22.2 No. 14 Product specifications

Type Optical sensors Electric connection type Plug-in connection Enclosure material Plastic Enclosure type Cuboid

Functions Color sensing

Short-circuit protection

Reflected-light beam Voltage type DC Wire size 0 Lamp type Other Output 3 NO PNP Outputs Connection type Plug-in connection M12 x 1

8 conductor Fiber optics core material Other Cable sheath material Other Light type White light

Other Degree of protection IP67

NEMA 4X LED indicator Status indication of Switching state: Yellow LED Switch function type Normally open contact (NO)

Laser protection class Other Operation agent-safety class Safety class 2 Shock resistance 30 g, Mechanical, Shock

duration 11 ms Optical surface material Glass Output current (mA) - max 100 mA Rated switching distance (Sn) 450 mm

Sensor height 50 mm Sensor length 50 mm Voltage rating - max 30 V Switching frequency 770 Hz Switching output type

PNP Vibration resistance 10 - 55 Hz, Amplitude 0.5 mm

According to IEC/EN 60068-2-6 Width sensor 25 mm Product category E76 IntelliView Serie...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E76-CLRMKP-M12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.