

INDUSTRIAL COMPONENT DATA

PFR-5-110AC 116963 EATON ELECTRIC Earth-leakage circuit-breaker 0, 03-5 A, 110AC

Brand: EATON - MOELLER | Manufacturer Part Number: PFR-5-110AC



Manufacturer	EATON - MOELLER
MPN / Reference	PFR-5-110AC
Catalog number	116963
Category	Residual current release for power circuit breaker
Minimum order	1 Pcs
Document ID	EO-3982DE5F7A
Generated	2026-08-06

Product Overview

Earth-leakage circuit-breaker 0, 03-5 A, 110AC

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Can be used for: NZM1, NZM1-4, N1, N1-4, NZM2, NZM2-4, N2, N2-4, NZM3, NZM3-4, N3, N3-4, NZM4, NZM4-4, N4-4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Earth-leakage circuit-breaker 0, 03-5 A, 110AC Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Can be used for: NZM1, NZM1-4, N1, N1-4, NZM2, NZM2-4, N2, N2-4, NZM3, NZM3-4, N3, N3-4, NZM4, NZM4-4, N4-4 [Delivery program

Rated fault currents [I_n] 0.03, 0.1, 0.3, 0.5, 1, 3, 5 A Description Adjustable fault current and delay time

Fault current early warning by flashing, red LED

Pulse-current sensitive

Integrated auxiliary contact (1 C/O)

Ring-type transformer must also be ordered

not UL/CSA approved Rated control voltage [U_s] 110 V AC 50/60Hz V Notes Adjustable fault current: 0.03, 0.1, 0.3, 0.5, 1, 3, 5 A

Adjustable delay time: 0.02, 0.1, 0.3, 0.5, 1, 3, 5 A

, Technical data

Electrical Standards IEC/EN 60947-2, IEC 755, IEC 1008, IEC 1009 Sensitivity Pulse current sensitive, type A Rated control voltage [Us] 110 ±20% (50/60 Hz) V AC Motor rating [Pe] 3 W Rated fault currents [I?n] 0.03, 0.1, 0.3, 0.5, 1, 3, 5 A Delay time [tv] 0.02, 0.1, 0.3, 0.5, 1, 3, 5 s Relay contacts 1 integrated changeover contact Rated voltage of the relay contact 250/100 V AC/DC Rated current of the relay contact 6 A Mechanical Standard front dimension 45 mm Enclosure height 85 mm Device width 45 mm Mounting Snap fixing, top-hat rail DIN 46277, IEC/EN 60715 Terminals top and bottom Box terminals Terminal protection Finger/back-of-hand pro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PFR-5-110AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.