

INDUSTRIAL COMPONENT DATA

PFR3-03-U 235869 Y7-235869 EATON ELECTRIC

Earth-leakage circuit-breaker, 25A, 300mA, type U

Brand: EATON - MOELLER | Manufacturer Part Number: PFR3-03-U



Manufacturer	EATON - MOELLER
MPN / Reference	PFR3-03-U
Catalog number	Y7-235869
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-D805DE0481
Generated	2026-08-05

Product Overview

Earth-leakage circuit-breaker, 25A, 300mA, type U

PFR3-03-U

Eaton Distribution parts. Earth-leakage circuit-breaker, 25A, 300mA, type U, 3

Specially matched residual current relay and ring-type transformer, rated fault currents 0.3 A and 1 A, standard (-S/A) and sensitive and selective (-U) type, auxiliary contact can be retrofitted, suitable for outdoor use (on-site power and outdoor distribution board) up to -25 °C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 235869 Model Code PFR3-03-U EAN 4015082358693 Product Length/Depth 80 mm Product Height 76 mm Product Width 70 mm Product Weight 0.301 kg Compliances RoHS conform Product specifications

Type Special features Ambient temperature hint: Starting at 40 °C, the max. permissible continuous current decreases by 3% for every 1 °C

Tripping signal contact for subsequent installation Z-NHK 248434

Amperage Rating 25 A Voltage rating 230 V AC / 400 V AC Features Selective protection

Additional equipment possible

Residual current relay Accessories required Z-HK 248432 10.10 Temperature rise The panel builder is responsible for the

temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to ab...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PFR3-03-U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.