

INDUSTRIAL COMPONENT DATA

EASY-BOX-802-SWD-USB 158461 EATON ELECTRIC Starter kit, EASY802-DC-SWD, EU4A-RJ45-USB-CAB1 and easySoft-Pro

Brand: EATON - MOELLER | Manufacturer Part Number: EASY-BOX-802-SWD-USB



Manufacturer	EATON - MOELLER
MPN / Reference	EASY-BOX-802-SWD-USB
Catalog number	158461
Category	PLC device set
Minimum order	1 Pcs
Document ID	EO-179C544046
Generated	2026-08-03

Product Overview

Starter kit, EASY802-DC-SWD, EU4A-RJ45-USB-CAB1 and easySoft-Pro

Starter kit; Includes (EASY802-DC-SWD, EU4A-RJ45-USB-CAB1, EASY-SOFT-PRO)

Starter kit to familiarize yourself with the efficient connecting technology of SmartWire-DT and the simple handling of the control relay EASY802-DC SmartWire-DT. SmartWire-DT enables a significant saving in time and costs when planning commissioning and maintenance. The starter kit includes the control relay EASY802-DC-SWD with SmartWire-DT, a programming cable for connecting the control relay to the USB interface of the computer. the programming software easySoft-Pro on CD as well as the documentation and manual as pdf. Up to 99 SmartWire-DT modules with a total of up to 166 inputs / outputs can be switched via a SmartWire-DT.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > EASY programmable relays and MFD displays
--------------	---

Additional Product Information

Starter kit, EASY802-DC-SWD, EU4A-RJ45-USB-CAB1 and easySoft-Pro Starter kit to familiarize yourself with the efficient connecting technology of SmartWire-DT and the simple handling of the control relay EASY802-DC SmartWire-DT.

SmartWire-DT enables a significant saving in time and costs when planning commissioning and maintenance. The starter kit includes the control relay EASY802-DC-SWD with SmartWire-DT, a programming cable for connecting the control relay to the USB interface of the computer. the programming software easySoft-Pro on CD as well as the documentation and manual as pdf. Up to 99 SmartWire-DT modules with a total of up to 166 inputs / outputs can be switched via a

SmartWire-DT. Delivery program

Product range Control relay easyRelay Basic function Starter kit Heat dissipation at 24 V DC Max. 5 W Note on heat dissipation Current consumption at 24 V DC (EASY802-DC-SWD) Technical data

General Standards EN 55011, EN 55022, IEC/EN 61000-4, IEC 60068-2-6, IEC 60068-2-27 Approvals CSA
UL

EAC Mounting Top-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1 (accessories)

Terminal capacities Solid 0.2/4 (AWG 22 - 12) mm² Flexible with ferrule 0.2/2.5 (AWG 22 - 12) mm² Climatic environmental conditions Operating ambient temperature In accordance with IEC 60068-2-1, -25 - +55 °C Condensation Take appropriate measures to prevent condensation relative humidity in accordance with IEC 60068-2-30, IEC 60068-2-78

5 - 95 % Air pressure (operation) 795 -...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY-BOX-802-SWD-USB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.