

INDUSTRIAL COMPONENT DATA

EASY-BOX-821-DC-BLT 172410 EATON ELECTRIC Starter kit consisting of EASY821-DC-TC with Bluetooth adapter eas..

Brand: EATON - MOELLER | Manufacturer Part Number: EASY-BOX-821-DC-BLT



Manufacturer	EATON - MOELLER
MPN / Reference	EASY-BOX-821-DC-BLT
Catalog number	172410
Category	PLC device set
Minimum order	1 Pcs
Document ID	EO-9EA7CD982A
Generated	2026-08-04

Product Overview

Starter kit consisting of EASY821-DC-TC with Bluetooth adapter easy800-BLT-ADP; EASY400-POW and easySoft-Basic Starter kit; Includes (EASY821-DC-TC, EASY800-BLT-ADP; EASY400-POW, EASY-SOFT-PRO)

Starter kit consisting of EASY821-DC-TC with Bluetooth adapter easy800-BLT-ADP

Starter kit for getting started with control engineering quickly and easily. The starter kit comes with an EASY821-DC-TC control relay, an easy400-POW switched-mode power supply unit, an easy800-BLT-ADP programming adapter, easySoft-Pro programming software on a CD, and documentation and a manual in PDF format.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > EASY programmable relays and MFD displays**

Additional Product Information

Starter kit consisting of EASY821-DC-TC with Bluetooth adapter easy800-BLT-ADP Starter kit for getting started with control engineering quickly and easily. The starter kit comes with an EASY821-DC-TC control relay, an easy400-POW switched-mode power supply unit, an easy800-BLT-ADP programming adapter, easySoft-Pro programming software on a CD, and documentation and a manual in PDF format. Delivery program

Product range Control relay easyRelay Basic function Starter kit Technical data

General Standards EN 55011, EN 55022, IEC/EN 61000-4, IEC 60068-2-6, IEC 60068-2-27 Approvals CSA

UL

EAC Mounting Top-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1 (accessories)

Terminal capacities Solid 0.2/4 (AWG 22 - 12) mm² Flexible with ferrule 0.2/2.5 (AWG 22 - 12) mm² Climatic environmental conditions Operating ambient temperature In accordance with IEC 60068-2-1, -25 - +55 °C Condensation Take appropriate

measures to prevent condensation relative humidity in accordance with IEC 60068-2-30, IEC 60068-2-78
5 - 95 % Air pressure (operation) 795 - 1080 hPa Ambient conditions, mechanical Protection type (IEC/EN 60529, EN50178, VBG 4) IP20 Vibrations In accordance with IEC 60068-2-6
constant amplitude 0.15 mm: 10 - 57
constant acceleration 2 g: 57 - 150 Hz Mechanical shock resistance (IEC/EN 60068-2-27) semi-sinusoidal 15 g/11 ms 18
Impacts Drop to IEC/EN 60068-2-31 [Drop height] 50 mm Free fall, packaged (IEC/EN 60068-2-32) 1 m Mounting position
Vertical or ho...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY-BOX-821-DC-BLT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.