

INDUSTRIAL COMPONENT DATA

EASY-BOX-E4-AC1 197229 Y7-197229 EATON ELECTRIC Starter package consisting of EASY-E4-AC-12RC1, patch cable ..

Brand: EATON - MOELLER | Manufacturer Part Number: EASY-BOX-E4-AC1



Manufacturer	EATON - MOELLER
MPN / Reference	EASY-BOX-E4-AC1
Catalog number	Y7-197229
Category	PLC device set
Minimum order	1 Pcs
Document ID	EO-09DABDFE6E
Generated	2026-08-05

Product Overview

Starter package consisting of EASY-E4-AC-12RC1, patch cable and software license for easySoft
EASY-BOX-E4-AC1

Eaton Moeller® series EASY Starter package consisting of EASY-E4-AC-12RC1, patch cable and software license for easySoft

Starter package for getting started with control engineering quickly and easily. The starter package contains the EASY-E4-AC-12RC1 control relay with LCD display and screw terminal connections, a patch cable for connecting the control relay to the Ethernet interface and a license for the easySoft operating and programming software.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Easy E4 Nanocontrollers
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series EASY Starter kit Catalog Number 197229 Model Code EASY-BOX-E4-AC1 EAN 4015080892908 Product Length/Depth 200 mm Product Height 135 mm Product Width 255 mm Product Weight 0.6 kg
Compliances Eaton supports the product until its end of life Certifications EN 55011

EN 55022

IEC/EN 61000-4

IEC/EN 61000-4-2

IEC 60068-2-6

IEC 60068-2-27 Catalog Notes depending on ambient air temperature fluctuations of up to ± 5 s/day (± 0.5 h/year) are possible Features & Functions

Fitted with: Basic device

Connection cable

Control unit

Software preinstalled

Programming software General

Insulation resistance According to EN 50178 Mounting method Screw fixing using fixing brackets ZB4-101-GF1 (accessories)

Top-hat rail fixing (according to IEC/EN 60715, 35 mm) Overvoltage category III Pollution degree 2 Type Starter kit Ambient conditions, mechanical

Drop and topple 50 mm Drop height, Drop to IEC/EN 60068-2-31 Mounting position Vertical

Horizontal Shock resistance 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 18 Impacts

Climatic environmental conditions

Air pressure 795 - 1080 hPa (operation) Environmental conditions Clearance in air and creepage distances according to EN 50178, UL 508, CSA C22.2, No. 142

Condensation: prevent with appropriate measures Relative humidity 5 - 95 % (IEC 60068-2-30, IEC 60068-2-78) Electro magnetic compatibility

Air discharge 8 kV Contact discharge 6 kV Immunity to line-conducted...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY-BOX-E4-AC1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.