

INDUSTRIAL COMPONENT DATA

EASY-BOX-E4-DCX-SWD1 199510 Y7-199510 EATON ELECTRIC EASY-BOX-E4-DCX-SWD1

Brand: EATON - MOELLER | Manufacturer Part Number: EASY-BOX-E4-DCX-SWD1



Manufacturer	EATON - MOELLER
MPN / Reference	EASY-BOX-E4-DCX-SWD1
Catalog number	Y7-199510
Category	PLC device set
Minimum order	1 Pcs
Document ID	EO-85D734C5A5
Generated	2026-08-02

Product Overview

EASY-BOX-E4-DCX-SWD1

Eaton EASY Bundle consisting of EASY-E4-DC-12TCX1 and EASY-COM-SWD-C1

Bundle for using the easyE4 as a SmartWire-DT coordinator, consisting of a DC base unit without display (EASY-E4-DC-12RCX1) and the SmartWire-DT communications module (EASY-COM-SWD-C1).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Easy E4 Nanocontrollers

Additional Product Information

General specifications

Product Name Eaton Moeller® series EASY Starter kit Catalog Number 199510 Model Code EASY-BOX-E4-DCX-SWD1
EAN 4015081980116 Product Length/Depth 200 mm Product Height 135 mm Product Width 255 mm Product Weight 0.6 kg
Compliances Eaton supports the product until its end of life Certifications IEC 60068-2-27

IEC/EN 61000-4

IEC 60068-2-6

EN 55022

EN 55011

IEC/EN 61000-4-2 Features & Functions

Fitted with: Connection cable

Documentation

Power supply General

Degree of protection IP20 Insulation resistance According to EN 50178 Mounting method Screw fixing using fixing brackets ZB4-101-GF1 (accessories)
Top-hat rail fixing (according to IEC/EN 60715, 35 mm) Overvoltage category III Pollution degree 2 Type Starter kit Ambient conditions, mechanical
Drop and topple 50 mm Drop height, Drop to IEC/EN 60068-2-31 Height of fall (IEC/EN 60068-2-32) - max 1 m Mounting position Horizontal
Vertical Shock resistance 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 18 Impacts Climatic environmental conditions
Air pressure 795 - 1080 hPa (operation) Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Environmental conditions Condensation: prevent with appropriate measures
Clearance in air and creepage distances according to EN 50178, UL 508, CSA C22.2, No. 142 Relative humidity 5 - 95 % (IEC 60068-2-30, IEC 60068-2-78) Electro magnetic compatibility
Air discharge 8 kV Contact discharge 6 kV, Electrostatic dis...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY-BOX-E4-DCX-SWD1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.