

INDUSTRIAL COMPONENT DATA

EASY-COM-RTU-M1 199453 Y7-199453 EATON ELECTRIC
EASY-COM-RTU-M1

Brand: EATON - MOELLER | Manufacturer Part Number: EASY-COM-RTU-M1



Manufacturer	EATON - MOELLER
MPN / Reference	EASY-COM-RTU-M1
Catalog number	Y7-199453
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-2160E35443
Generated	2026-08-02

Product Overview

EASY-COM-RTU-M1

Eaton EASY Communication module for connecting the easy control relay via Modbus RTU Server, screw terminal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Easy E4 Nanocontrollers

Additional Product Information

General specifications

Product Name Eaton Moeller® series EASY Accessory Bus module Catalog Number 199453 Model Code

EASY-COM-RTU-M1 EAN 4015081978441 Product Length/Depth 58 mm Product Height 90 mm Product Width 36 mm

Product Weight 0.1 kg Certifications IEC/EN 61000-6-3

IEC/EN 61000-4-2

EN 61010

CE

IEC 60068-2-27

IEC/EN 61000-6-2

EN 50178

IEC 60068-2-6

IEC/EN 61131-2

IEC 60068-2-30

UL Listed

UL File No.: E205091

UL hazardous location class I

UL hazardous location division 2

UL hazardous location group A (acetylene)

UL hazardous location group B (hydrogen)

UL hazardous location group C (ethylene)

UL hazardous location group D (propane) Features & Functions

Features Expandable

Expansion device General

Degree of protection IP20 Insulation resistance According to EN 50178, EN 61010-2-201, UL61010-2-201, CSA-C22.2 NO.

61010-2-201 Mounting method Rail mounting possible

Screw fixing using fixing brackets ZB4-101-GF1 (accessories)

Top-hat rail fixing (according to IEC/EN 60715, 35 mm)

Wall mounting/direct mounting

Front build in possible Overvoltage category II Pollution degree 2 Protocol MODBUS

TCP/IP Type Communication module Voltage type DC Ambient conditions, mechanical

Drop and topple 50 mm Drop height, Drop to IEC/EN 60068-2-31 Mounting position Vertical

Horizontal Shock resistance 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 18 Impacts

Climatic environmental conditions

Air pressure 795 - 1080 hPa (operation) Ambient operating temperature -....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY-COM-RTU-M1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.