

INDUSTRIAL COMPONENT DATA

EASY-E4-AC-12RC1 197215 Y7-197215 EATON ELECTRIC Control relays, easyE4 (expandable, Ethernet), 100 240 V AC..

Brand: EATON - MOELLER | Manufacturer Part Number: EASY-E4-AC-12RC1



Manufacturer	EATON - MOELLER
MPN / Reference	EASY-E4-AC-12RC1
Catalog number	Y7-197215
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-BD21DF64E7
Generated	2026-08-06

Product Overview

Control relays, easyE4 (expandable, Ethernet), 100 - 240 V AC, 110 - 240 V DC, Inputs Digital: 8, Outputs Digital: 4 relays, screw terminal

EASY-E4-AC-12RC1

Eaton Moeller® series EASY Control relays easyE4 with display (expandable, Ethernet), 100 - 240 V AC, 110 - 220 V DC (cULus: 100 - 110 V DC), Inputs Digital: 8, screw terminal EASY-E4-AC-12RC1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Easy E4 Nanocontrollers
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series EASY Control relay Catalog Number 197215 Model Code EASY-E4-AC-12RC1 EAN 4015081939442 Product Length/Depth 58 mm Product Height 90 mm Product Width 72 mm Product Weight 0.25 kg
Compliances Eaton supports the product until its end of life Certifications EN 61010

IEC/EN 61000-6-2

CULus per UL 61010

IEC/EN 61000-4-2

IEC/EN 61131-2

IEC 60068-2-30

CSA-C22.2 No. 61010

EN 50178

IEC 60664
IEC 60068-2-27
IEC 60068-2-6
IEC/EN 61000-6-3
UL Listed
UL Category Control No.: NRAQ, NRAQ7
UL File No.: E205091
DNV GL
CE
UL hazardous location class I
UL hazardous location division 2
UL hazardous location group A (acetylene)
UL hazardous location group B (hydrogen)
UL hazardous location group C (ethylene)
UL hazardous location group D (propane) Catalog Notes Accuracy of the real-time clock depending on ambient air temperature - fluctuations of up to ± 5 s/day (± 0.5 h/year) are possible Features & Functions
Features Networkable (Ethernet)
Expandable
Display indication of 6 lines x 16 characters Fitted with: Relay output
Timer
Keypad
Display
Real time clock Indication LCD-display used as status indication of Digital inputs 115/230 V AC General
Degree of protection IP20 Display temperature - min 0 °C Display temperature - max 55 °C Display type Monochrome Input frequency 50/60 Hz (Digital inputs, at 115/230 V AC)
50/60 Hz (Digital inputs, at 24 V DC) Insulation resistance According to EN 50178, EN 61010-2-201, UL61010-2-201, CSA-C22.2 NO....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY-E4-AC-12RC1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.