

INDUSTRIAL COMPONENT DATA

EASY-E4-DC-6AE1 197223 Y7-197223 EATON ELECTRIC I/O expansion, For use with easyE4, 24 V DC, Inputs expansio..

Brand: EATON - MOELLER | Manufacturer Part Number: EASY-E4-DC-6AE1



Manufacturer	EATON - MOELLER
MPN / Reference	EASY-E4-DC-6AE1
Catalog number	Y7-197223
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-2E7FF15788
Generated	2026-08-04

Product Overview

I/O expansion, For use with easyE4, 24 V DC, Inputs expansion (number) analog: 4, Outputs expansion (number) digital: 2, screw terminal

EASY-E4-DC-6AE1

Eaton Moeller® series EASY I/O expansion, For use with easyE4, 24 V DC, Inputs expansion (number) analog: 4, screw terminal EASY-E4-DC-6AE1

I/O expansion, Supply voltage: 24 V DC, Can be used via easyConnect, Mounting position: Vertical or horizontal, Protection type (IEC/EN 60529, EN50178, VBG 4): IP20, Standards: EN 61000-6-2, EN 61000-6-3, IEC 60068-2-6, IEC 60068-2-27, IEC 60068-2-30, IEC 61131-2, EN 61010, EN 50178, cULus per UL 61010, CSA C22.2 No.61010

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Easy E4 Nanocontrollers
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series EASY I/O expansion Catalog Number 197223 Model Code EASY-E4-DC-6AE1 EAN 4015080892847 Product Length/Depth 58 mm Product Height 90 mm Product Width 36 mm Product Weight 0.1 kg

Certifications CSA-C22.2 No. 61010

IEC/EN 61000-4-2

EN 61010

IEC/EN 61131-2

IEC/EN 61000-6-2

EN 50178

IEC/EN 61000-6-3

CULus per UL 61010

IEC 60068-2-27

IEC 60068-2-30

IEC 60068-2-6

UL Listed

UL Category Control No.: NRAQ, NRAQ7

UL File No.: E205091

DNV GL

CE

UL hazardous location class I

UL hazardous location division 2

UL hazardous location group A (acetylene)

UL hazardous location group B (hydrogen)

UL hazardous location group C (ethylene)

UL hazardous location group D (propane) Features & Functions

Features Expandable

Expansion device General

Degree of protection IP20 Insulation resistance According to EN 50178, EN 61010-2-201, UL61010-2-201, CSA-C22.2 NO.

61010-2-201 Mounting method Front build in possible

Rail mounting possible

Wall mounting/direct mounting

Top-hat rail fixing (according to IEC/EN 60715, 35 mm)

Screw fixing using fixing brackets ZB4-101-GF1 (accessories) Overvoltage category III Pollution degree 2 Product category

Control relays easyE4 Protocol TCP/IP

MODBUS Residual ripple $\leq 5\%$ Resolution Software EASYSOFT-SWLIC/easySoft7 Type easyE4 extension Voltage type

DC Ambient conditions, mechanical

Drop and topple 50 mm Drop height, Drop to IEC/EN 60068-2-31 Height of fall (IEC/EN 60068-2-32) - max 0.3 m Mounting position Horizon...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY-E4-DC-6AE1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.