

INDUSTRIAL COMPONENT DATA

EASY-E4-UC-8RE1 197217 Y7-197217 EATON ELECTRIC I/O expansion, For use with easyE4, 12/24 V DC, 24 V AC, Inp..

Brand: EATON - MOELLER | Manufacturer Part Number: EASY-E4-UC-8RE1



Manufacturer	EATON - MOELLER
MPN / Reference	EASY-E4-UC-8RE1
Catalog number	Y7-197217
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-697768E5A6
Generated	2026-08-04

Product Overview

I/O expansion, For use with easyE4, 12/24 V DC, 24 V AC, Inputs/Outputs expansion (number) digital: 4, screw terminal EASY-E4-UC-8RE1

Eaton Moeller® series EASY I/O expansion, For use with easyE4, 12/24 V DC, 24 V AC, Inputs expansion (number) digital: 4, screw terminal

I/O expansion, Supply voltage: 12/24 V DC, 24 V AC, Can be used via easyConnect, Mounting position: Vertical or horizontal, Protection type (IEC/EN 60529, EN50178, VBG 4): IP20, Standards: EN 61000-6-2, EN 61000-6-3, IEC 60068-2-6, IEC 60068-2-27, IEC 60068-2-30, IEC 61131-2, EN 61010, EN 50178, cULus per UL 61010, CSA C22.2 No.61010

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Easy E4 Nanocontrollers
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series EASY I/O expansion Catalog Number 197217 Model Code EASY-E4-UC-8RE1 EAN 4015080892786 Product Length/Depth 58 mm Product Height 90 mm Product Width 36 mm Product Weight 0.125 kg

Certifications CULus per UL 61010

IEC 60068-2-6

IEC 60068-2-27

IEC/EN 61000-6-3

CSA-C22.2 No. 61010

IEC 60068-2-30

EN 61010

IEC/EN 61131-2

EN 50178

IEC/EN 61000-4-2

IEC/EN 61000-6-2

UL Listed

UL Category Control No.: NRAQ, NRAQ7

UL File No.: E205091

DNV GL

CE

UL hazardous location class I

UL hazardous location division 2

UL hazardous location group A (acetylene)

UL hazardous location group B (hydrogen)

UL hazardous location group C (ethylene)

UL hazardous location group D (propane) Catalog Notes fitted with two controlled relays Features & Functions

Features Expandable

Expansion device Fitted with: Relay output Indication LCD-display base unit used as status indication of Digital inputs 12 V DC

LCD-display base unit used as status indication of Digital inputs 24 V DC General

Degree of protection IP20 Input frequency 50/60 Hz (Digital inputs, at 24 V DC) Insulation resistance According to EN 50178, EN 61010-2-201, UL61010-2-201, CSA-C22.2 NO. 61010-2-201 Lifespan, electrical 25,000 Operations (Filament bulb load at 500 W, 115/120 V AC)

25,000 Operations (Fluorescent lamp load 10 x 58 W at 230/240 V AC, uncompensated)

25,000 Operations (Fluorescent lamp load 1 x 58 W at 230/240 V AC, conventional, compensated)

25,000 Operations (Fluorescent lamp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY-E4-UC-8RE1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.