

INDUSTRIAL COMPONENT DATA

EASY200-POW 229424 0004520990 EATON ELECTRIC

Switched-mode power supply unit, 100-240VAC/24VDC/12VDC, 0.35A/..

Brand: EATON - MOELLER | Manufacturer Part Number: EASY200-POW



Manufacturer	EATON - MOELLER
MPN / Reference	EASY200-POW
Catalog number	0004520990
Category	PLC system power supply
Minimum order	1 Pcs
Document ID	EO-63EFBB77DA
Generated	2026-08-05

Product Overview

Switched-mode power supply unit, 100-240VAC/24VDC/12VDC, 0.35A/0.02A, 1-phase, controlled
EASY200-POW

The primary cycled and controlled switched-mode power supply units supply a safe low voltage (SELV according to EN60950) with radio interference level B according to EN55011 and EN55022. They have been tested for use in industrial as well as public networks. Overload safety and permanent short-circuit strength ensure for a high safety of the devices. Rated input voltage at 50/60 Hz: 100-240VAC, rated output voltage: 24V/12VDC, rated output current: 0.35A/20 mA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

Additional Product Information

General specifications

Product Name Eaton easyPOW power supply unit Catalog Number 229424 Model Code EASY200-POW EAN 4015082294243 Product Length/Depth 58 mm Product Height 90 mm Product Width 36 mm Product Weight 0.085 kg
Certifications CE

UL Category Control No.: NRAQ

CSA-C22.2 No. 213-M1987

IEC 60068-2-27

UL File No.: E135462

EN 55022

CSA Class No.: 2252-01 + 2258-02

CSA File No.: 012528

CSA

UL

IEC 60068-2-6

EN 55011

IEC/EN 61000-4

CSA-C22.2 No. 142-M1987

UL 508 Features & Functions

Features Overload proof (by current limitation)

Proof against sustained short circuit, hiccup mode (Output current 24 V DC) Number of phases 1 General

Degree of Protection IP20 (according to IEC/EN 60529, EN 50178, VBG 4) Mounting Method Screw fixing using fixing brackets ZB4-101-GF1 (accessories)

Top-hat rail fixing (according to IEC/EN 60715, 35 mm) Product category Control relays easyE4 Used with easyE4 LED indicator Status Indication of 24 V DC output voltage: Continuous green light LED Power consumption 7 W typ. Ambient conditions, mechanical

Mounting position Vertical

Horizontal Shock resistance 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 18 Impacts

Climatic environmental conditions

Altitude Max. 2000 m Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 70 °C Electro magnetic compatibility

Air discharge 8 kV, according to IEC/EN 61000-4-2, Level 3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY200-POW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.