

INDUSTRIAL COMPONENT DATA

EASY430-POW 110940 EATON ELECTRIC Switched-mode power supply unit, 100-240VAC/24VDC, 1.25A, 1-phase, control..

Brand: EATON - MOELLER | Manufacturer Part Number: EASY430-POW



Manufacturer	EATON - MOELLER
MPN / Reference	EASY430-POW
Catalog number	110940
Category	PLC system power supply
Minimum order	1 Pcs
Document ID	EO-4A125F0F43
Generated	2026-08-02

Product Overview

Switched-mode power supply unit, 100-240VAC/24VDC, 1.25A, 1-phase, controlled

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

Additional Product Information

Switched-mode power supply unit, 100-240VAC/24VDC, 1.25A, 1-phase, controlled The primary cycled and controlled switched-mode power supply units supply a safe low voltage (SELV according to EN60950) with radio interference level B according to EN55011 and EN55022. They have been tested for use in industrial as well as public networks. Overload safety and permanent short-circuit strength ensure for a high safety of the devices. Rated input voltage at 50/60 Hz: 100-240VAC, rated output voltage: 24VDC with a residual ripple of $\pm 3\%$ rated output current: 1.25A, can be switched in parallel to increase power outputs [Delivery program

Product range Control relay easyRelay

Multi-function-display MFD-Titan Product range Switched-mode power supply units easyPOW Description primary chopper controlled Phases Single-phase Input voltage range 85 - 264 V AC Nominal input voltage 100 - 240 V AC Rated output voltage 24 V DC ($\pm 3\%$) Rated output current 1.25 A For use with easy500

easy700

easy800

MFD-CP8

EC4P

ES4P Description Rated input voltage: 50/60 HZ: 115/230 V AC

Rated output voltage (residual ripple): 24 V DC ($\pm 3\%$)

Rated output current: 1.25 A

Can be connected directly in parallel

, Technical data

General Standards EN 55011, EN 55022, IEC/EN 61000-4, IEC 60068-2-6, IEC 60068-2-27 Dimensions (W x H x D) 71.5 (4 PE) x 90 x 58 mm Weight 0.25 kg Mounting Top-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1 (accessories) Terminal capacities Solid 0.2/4 (AWG 22...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY430-POW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.