

INDUSTRIAL COMPONENT DATA

EASY-BOX-512-DC-USB 116563 EATON ELECTRIC Starter kit, EASY512-DC-RC, EASY200-POW, EASY-USB-CAB and easySoft..

Brand: EATON - MOELLER | Manufacturer Part Number: EASY-BOX-512-DC-USB



Manufacturer	EATON - MOELLER
MPN / Reference	EASY-BOX-512-DC-USB
Catalog number	116563
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-097E861CA7
Generated	2026-08-01

Product Overview

Starter kit, EASY512-DC-RC, EASY200-POW, EASY-USB-CAB and easySoft-Basic
Starter kit; Includes (EASY512-DC-RC, EASY200-POW, EASY-USB-CAB, EASY-SOFT-BASIC)
EASY-BOX-512-DC-USB

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > EASY programmable relays and MFD displays
--------------	---

Additional Product Information

Starter kit, EASY512-DC-RC, EASY200-POW, EASY-USB-CAB and easySoft-Basic Starter kit for the easy access to the safety control engineering. The starter kit includes the control relay EASY512-DC-RC and a switched-mode power supply unit easy200-POW, the programming cable easy-USB-CAB for connecting the control relay to the USB interface of the computer, the programming software easySoft-Basic on CD as well as the documentation and manual as pdf. 8 digital inputs, 4 output signals (relay 8A) are available. Delivery program

Product range Control relay easyRelay Basic function Starter kit Heat dissipation at 24 V DC 2 W Technical data
General Standards EN 55011, EN 55022, IEC/EN 61000-4, IEC 60068-2-6, IEC 60068-2-27 Approvals CSA
UL

EAC Mounting Top-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1 (accessories)

Terminal capacities Solid 0.2/4 (AWG 22 - 12) mm² Flexible with ferrule 0.2/2.5 (AWG 22 - 12) mm² Climatic environmental conditions Operating ambient temperature In accordance with IEC 60068-2-1, -25 - +55 °C Condensation Take appropriate

measures to prevent condensation relative humidity in accordance with IEC 60068-2-30, IEC 60068-2-78
5 - 95 % Air pressure (operation) 795 - 1080 hPa Ambient conditions, mechanical Protection type (IEC/EN 60529,
EN50178, VBG 4) IP20 Vibrations In accordance with IEC 60068-2-6
constant amplitude 0.15 mm: 10 - 57
constant acceleration 2 g: 57 - 150 Hz Mechanical shock resistance (IEC/EN 60068-2-27) semi-sinuso...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY-BOX-512-DC-USB with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.