

INDUSTRIAL COMPONENT DATA

MFD-XM-80 265258 EATON ELECTRIC Protective diaphragm for MFD-80-B, increases the housing's protection type t..

Brand: EATON - MOELLER | Manufacturer Part Number: MFD-XM-80



Manufacturer	EATON - MOELLER
MPN / Reference	MFD-XM-80
Catalog number	265258
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-5964BEF911
Generated	2026-08-02

Product Overview

Protective diaphragm for MFD-80-B, increases the housing's protection type to NEMA 4x, transparent Protective Cover for MFD-80...

Protective diaphragm in transparent version for harsh environmental conditions and application in the food industry, can be used for MFD-80..., the degree of protection is increased to NEMA 80x with MFD-4-B

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > EASY programmable relays and MFD displays
--------------	---

Additional Product Information

Protective diaphragm for MFD-80-B, increases the housing's protection type to NEMA 4x, transparent Protective diaphragm in transparent version for harsh environmental conditions and application in the food industry, can be used for MFD-80..., the degree of protection is increased to NEMA 80x with MFD-4-B Delivery program

Product range Multi-function-display MFD-Titan Accessories Protective diaphragm Description Transparent version for harsh environmental conditions and application in the food industry

For increasing the degree of protection to NEMA 4X for MFD-80-B For use with MFD-80... Information relevant for export to North America Product Standards IEC/EN see Technical Data; UL 508; CSA C22.2 No. 142-M1987; CSA C22.2 No. 213-M1987; CE marking

UL File No. E135462

UL Category Control No. NRAQ

CSA File No. 012528

CSA Class No. 2252-01 + 2258-02

North America Certification UL listed, CSA certified

Degree of Protection IEC: IP65, UL/CSA Type 4X

Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [In] 0 A Heat dissipation per pole, current-dependent [Pvid] 0 W Equipment heat dissipation, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 0 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -25 °C Operating ambient temperature max. +55 °C IEC/EN 61439 design verification 10.2 Strength of materials and parts 10.2.2 Corrosion resistance Meets the p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MFD-XM-80 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.