

INDUSTRIAL COMPONENT DATA

MFD-TAP13-PT-A 106045 0004519717 EATON ELECTRIC I/O module with temperature measuring, range A, 6DI(2AI), 2I..

Brand: EATON - MOELLER | Manufacturer Part Number: MFD-TAP13-PT-A



Manufacturer	EATON - MOELLER
MPN / Reference	MFD-TAP13-PT-A
Catalog number	0004519717
Category	PLC analogue I/O-module
Minimum order	1 Pcs
Document ID	EO-6B3CE8DEC5
Generated	2026-08-05

Product Overview

I/O module with temperature measuring, range A, 6DI(2AI), 2I-Pt100, 4DO-Trans, 1AO
Temperature MFD I/O Module; 24 V DC; 2 Pt100 (Rank A), 6ED(2EA), 4SD, 1SA; For MFD-CP8/CP10
I/O module with temperature measuring, power supply 24 VDC, is snapped onto MFD-AC-CP8 beginning with device version 08/CP10, 6 digital inputs of which 2 inputs are available as analog inputs, 2 inputs as temperature inputs with Pt100, 4 transistor outputs, 1 analog output, configurable temperature range: -40up to+90/0up to+250/0up to+400 °C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > EASY programmable relays and MFD displays
--------------	---

Additional Product Information

I/O module with temperature measuring, range A, 6DI(2AI), 2I-Pt100, 4DO-Trans, 1AO I/O module with temperature measuring, power supply 24 VDC, is snapped onto MFD-AC-CP8 beginning with device version 08/CP10, 6 digital inputs of which 2 inputs are available as analog inputs, 2 inputs as temperature inputs with Pt100, 4 transistor outputs, 1 analog output, configurable temperature range: -40up to+90/0up to+250/0up to+400 °C Delivery program

Description Configurable temperature range Supply voltage 24 V DC Inputs Digital 6 of which can be used as analog 2 Pt100, Pt1000, Ni1000 2 Outputs Transistor 4 Analog 1 Temperature range Temperature detector -40...+90 °C 0...+250 °C

0...+400 °C For use with MFD-CP8... from device version 08

MFD-CP10.. Technical data

General Standards EN 61000-6-1/-2/-3/-4, IEC 60068-2-6, IEC 60068-2-27 Dimensions (W x H x D) 89 x 90 x 25 (installed) mm Weight 0.14 kg Mounting Fitted into the power supply unit. Terminal capacities Solid 0.2/4 (AWG 24 - 12) mm2 Flexible

with ferrule 0.2/2.5 (AWG 24 - 12) mm² Standard screwdriver 3.5 x 0.6 mm Climatic environmental conditions Operating ambient temperature -25 to 55, cold as per IEC 60068-2-1, heat as per IEC 60068-2-2 °C Condensation Take appropriate measures to prevent condensation Storage - 40 - 70 °C Relative humidity, non-condensing (IEC/EN 60068-2-30) 5 - 95 % Air pressure (operation) 795 - 1080 hPa Ambient conditions, mechanical Pollution degree 2 Protection type (IEC/EN 60529, EN50178, VBG 4) IP20 Vibrations....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MFD-TAP13-PT-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.