

INDUSTRIAL COMPONENT DATA

MFD-CP10-ME 133801 0004560809 EATON ELECTRIC Central processing unit/power supply unit, 24 V DC, expandable,...

Brand: EATON - MOELLER | Manufacturer Part Number: MFD-CP10-ME



Manufacturer	EATON - MOELLER
MPN / Reference	MFD-CP10-ME
Catalog number	0004560809
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-FF6C40DE43
Generated	2026-08-04

Product Overview

Central processing unit/power supply unit, 24 V DC, expandable, without easyNet, double memory like MFD-CP 8
MFD-Titan Graphic Programmable Relay; 24 V DC; Without EasyNet; Dual memory than MFD-CP8
Power supply unit, Subrange: CPU modules, Degree of Protection: IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

Additional Product Information

EL-Nummer (Norway)4560809Central processing unit/power supply unit, 24 V DC, expandable, without easyNet, double memory like MFD-CP 8Power supply unit, Subrange: CPU modules, Degree of Protection: IP20Delivery program
Product rangeMulti-function-display MFD-TitanBasic functionPower supply unit/CPU modulesSubrangeCPU modulesSupply voltage24 V DCEasyNet/easyLinkohne easyNet

Descriptioncan be combined with display/operating unit MFD-80-.. and I/O module

Expandable: Digital/analog inputs/outputs and AS-Interface, PROFIBUS-DP, CANopen®, DeviceNet bus systems

Bussystem easyNet optional on board

Program and screen memory

Delivery with user program possible with MFD-COMBINATION product (Article no. 201801)Descriptiondouble program and screen memory like MFD-CP8...Connection typescrew terminalDegree of ProtectionIP20Technical data

GeneralStandardsEN 61000-6-1/-2/-3/-4, IEC 60068-2-6, IEC 60068-2-27Dimensions (W x H x D)107.5 x 90 x 30

mmWeight0.145 kgMountingFitted on the fixing shaft of the display or on top-hat rail according to IEC/EN 60715, 35 mm deep (without display)Terminal capacitiesSolid0.2/4 (AWG 24 - 12) mm2Flexible with ferrule0.2/2.5 (AWG 24 - 12)

mm2Standard screwdriver3.5 x 0.6 mmClimatic environmental conditionsOperating ambient temperature-25 to 55, cold as per IEC 60068-2-1, heat as per IEC 60068-2-2 °CCondensationTake appropriate measures to prevent condensationStorage- 40 - 70 °CRelative humidity, non-condensing (IEC/EN 60068-2-30)5 - 95 %Air pressure (operation)795...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MFD-CP10-ME with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.