

INDUSTRIAL COMPONENT DATA

MFD-CP10-NT 133800 0004560808 EATON ELECTRIC Central processing unit/power supply unit, 24 V DC, expandable,..

Brand: EATON - MOELLER | Manufacturer Part Number: MFD-CP10-NT



Manufacturer	EATON - MOELLER
MPN / Reference	MFD-CP10-NT
Catalog number	0004560808
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-E017B8A118
Generated	2026-08-04

Product Overview

Central processing unit/power supply unit, 24 V DC, expandable, with easyNet, double memory like MFD-CP 8
MFD-Titan Graphic Programmable Relay; 24 V DC; With EasyNet; Dual memory than MFD-CP8
Power supply unit, Subrange: CPU modules, Degree of Protection: IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > EASY programmable relays and MFD displays**

Additional Product Information

EL-Nummer (Norway)4560808Central processing unit/power supply unit, 24 V DC, expandable, with easyNet, double memory like MFD-CP 8Power supply unit, Subrange: CPU modules, Degree of Protection: IP20Delivery program
Product rangeMulti-function-display MFD-TitanBasic functionPower supply unit/CPU modulesSubrangeCPU modulesSupply voltage24 V DCEasyNet/easyLinkmit easyNet
Descriptioncan be combined with display/operating unit MFD-80-.. and I/O module
Expandable: Digital/analog inputs/outputs and AS-Interface, PROFIBUS-DP, CANopen®, DeviceNet bus systems
Bussystem easyNet optional on board
Program and screen memory
Delivery with user program possible with MFD-COMBINATION product (Article no. 201801)DescriptionDouble program and screen memory, as MFD-CP8..., with easyNetConnection typescrew terminalDegree of ProtectionIP20Technical data
GeneralStandardsEN 61000-6-1/-2/-3/-4, IEC 60068-2-6, IEC 60068-2-27Dimensions (W x H x D)107.5 x 90 x 30 mmWeight0.145 kgMountingFitted on the fixing shaft of the display or on top-hat rail according to IEC/EN 60715, 35 mm deep (without display)Terminal capacitiesSolid0.2/4 (AWG 24 - 12) mm2Flexible with ferrule0.2/2.5 (AWG 24 - 12)

mm2Standard screwdriver3.5 x 0.6 mmClimatic environmental conditionsOperating ambient temperature-25 to 55, cold as per IEC 60068-2-1, heat as per IEC 60068-2-2 °CCondensationTake appropriate measures to prevent condensationStorage- 40 - 70 °CRelative humidity, non-condensing (IEC/EN 60068-2-30)5 - 95 %Air pressure (oper...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MFD-CP10-NT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.