

## INDUSTRIAL COMPONENT DATA

# MFD-CP8-NT 265253 0004519703 EATON ELECTRIC Central processing unit/power supply unit, 24 V DC, expandable, ..

Brand: EATON - MOELLER | Manufacturer Part Number: MFD-CP8-NT



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | MFD-CP8-NT      |
| Catalog number  | 0004519703      |
| Category        | Graphic panel   |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-2DA987A7C7   |
| Generated       | 2026-08-05      |

## Product Overview

Central processing unit/power supply unit, 24 V DC, expandable, with easyNet, program and screen memory

MFD-Titan Graphic Programmable Relay; 24 V DC; With EasyNet

Power supply module, Subrange: CPU modules, Degree of Protection: IP20

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

## Additional Product Information

Central processing unit/power supply unit, 24 V DC, expandable, with easyNet, program and screen memory Power supply module, Subrange: CPU modules, Degree of Protection: IP20 Delivery program

Product range Multi-function-display MFD-Titan Basic function Power supply unit/CPU modules Subrange CPU modules

Supply voltage 24 V DC easyNet/easyLink mit easyNet

Description can be combined with display/operating unit MFD-80-.. and I/O module

Expandable: Digital/analog inputs/outputs and AS-Interface, PROFIBUS-DP, CANopen®, DeviceNet bus systems

Bussystem easyNet optional on board

Program and screen memory

Delivery with user program possible with MFD-COMBINATION product (Article no. 201801) Description Program and screen memory, with easyNet Connection type Spring-cage terminals Degree of Protection IP20 Technical data

General Standards EN 61000-6-1/-2/-3/-4, IEC 60068-2-6, IEC 60068-2-27 Dimensions (W x H x D) 107.5 x 90 x 30 mm

Weight 0.145 kg Mounting Fitted on the fixing shaft of the display or on top-hat rail according to IEC/EN 60715, 35 mm deep (without display) Terminal capacities Solid 0.2/4 (AWG 24 - 12) mm2 Flexible with ferrule 0.2/2.5 (AWG 24 - 12) mm2

Standard screwdriver 3.5 x 0.6 mm Climatic environmental conditions Operating ambient temperature -25 to 55, cold as per IEC 60068-2-1, heat as per IEC 60068-2-2 °C Condensation Take appropriate measures to prevent condensation Storage - 40 - 70 °C Relative humidity, non-condensing (IEC/EN 60068-2-30) 5 - 95 % Air pressure...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MFD-CP8-NT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.