

INDUSTRIAL COMPONENT DATA

EASY200-EASY 212315 0004520910 EATON ELECTRIC

Control relay coupling module to the decentralized connection ..

Brand: EATON - MOELLER | Manufacturer Part Number: EASY200-EASY



Manufacturer	EATON - MOELLER
MPN / Reference	EASY200-EASY
Catalog number	0004520910
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-0A3A3EEC26
Generated	2026-08-03

Product Overview

Control relay coupling module to the decentralized connection of a dig. extension, easyLink
Easy Module; To decentralize I/O expansions up to 30 m
Control relay expansion to the decentralized connection of a digital I/O expansion up to 30 m, can be used through easyLink

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > EASY programmable relays and MFD displays
--------------	---

Additional Product Information

Control relay coupling module to the decentralized connection of a dig. extension, easyLink Control relay expansion to the decentralized connection of a digital I/O expansion up to 30 m, can be used through easyLink Delivery program
Product range Control relay easyRelay
Multi-function-display MFD-Titan Product range Compact PLCs Basic function Expansions Function Expansions EASY...
Accessories Coupling module Description Can be used through easyLink Function Fir remote connection of a digital I/O extension up to 30 m. For use with easy700
easy800
EC4P
MFD-CP8..
ES4P Technical data
General Standards EN 55011, EN 55022, IEC/EN 61000-4, IEC 60068-2-6, IEC 60068-2-27 Dimensions (W x H x D) 35.5 x

90 x 58 (2 PE) mm Weight 0.07 kg Mounting Top-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1 (accessories) Terminal capacities Solid 0.2/4 (AWG 22 - 12) mm² Flexible with ferrule 0.2/2.5 (AWG 22 - 12) mm² Standard screwdriver 0.8 x 3.5 mm Max. tightening torque 0.6 Nm Climatic environmental conditions Operating ambient temperature -25 to 55, cold as per IEC 60068-2-1, heat as per IEC 60068-2-2 °C Condensation Take appropriate measures to prevent condensation LCD display (clearly legible) 0 - 55 °C Storage - 40 - 70 °C Relative humidity, non-condensing (IEC/EN 60068-2-30) 5 - 95 % Air pressure (operation) 795 - 1080 hPa Corrosion resistance IEC/EN 60068-2-42 [4 days SO₂] 10 cm³/m³ Corrosion resistance IEC/EN 60068-2-43 [4 days H₂S] 1 cm³/m³ Ambient conditions,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY200-EASY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.