

INDUSTRIAL COMPONENT DATA

MFD-AC-CP4 286822 0004560852 EATON ELECTRIC

Communication module/power supply unit for remote text display, ..

Brand: EATON - MOELLER | Manufacturer Part Number: MFD-AC-CP4



Manufacturer	EATON - MOELLER
MPN / Reference	MFD-AC-CP4
Catalog number	0004560852
Category	Text panel
Minimum order	1 Pcs
Document ID	EO-E8601A41D4
Generated	2026-08-03

Product Overview

Communication module/power supply unit for remote text display, 100-240VAC, easy/EC4P/ES4P

CPU Text Module; For remote display; 100-240 V AC; Cordless; For EASY, EC4P, ES4P

Together with the display and operating unit MFD-80..., the power supply unit / communication module can be used as remote text display for easy500 / easy700 / easy800 / EC4P / ES4P, enclosure degree of protection IP20, without connection cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

Additional Product Information

Communication module/power supply unit for remote text display, 100-240VAC, easy/EC4P/ES4P Together with the display and operating unit MFD-80..., the power supply unit / communication module can be used as remote text display for easy500 / easy700 / easy800 / EC4P / ES4P, enclosure degree of protection IP20, without connection cable Delivery program

Product range Multi-function-display MFD-Titan Product range Compact PLCs Basic function Power supply unit/CPU modules Function Accessories Accessories Remote text display Supply voltage 100 - 240 V AC Description Degree of protection IP20 can be combined with display/operating unit MFD-80...

as detachable touch display for easyRelais Description Without connection cable Degree of Protection IP20 Technical data General Standards EN 61000-6-1/-2/-3/-4, IEC 60068-2-6, IEC 60068-2-27 Dimensions (W x H x D) 107.5 x 90 x 30 mm

Weight 0.145 kg Mounting Fitted on the fixing shaft of the display or on top-hat rail according to IEC/EN 60715, 35 mm deep (without display) Terminal capacities Solid 0.2/4 (AWG 24 - 12) mm² Flexible with ferrule 0.2/2.5 (AWG 24 - 12) mm² Standard screwdriver 3.5 x 0.6 mm Climatic environmental conditions Operating ambient temperature -25 to 55, cold as per IEC 60068-2-1, heat as per IEC 60068-2-2 °C Condensation Take appropriate measures to prevent condensation Storage -40 - 70 °C Relative humidity, non-condensing (IEC/EN 60068-2-30) 5 - 95 % Air pressure (operation) 795 - 1080 hPa Ambient conditions, mechan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MFD-AC-CP4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.