

INDUSTRIAL COMPONENT DATA

MFD-CP4 280888 0004560921 EATON ELECTRIC

Communication module/power supply unit for remote text display, 24 ..

Brand: EATON - MOELLER | Manufacturer Part Number: MFD-CP4



Manufacturer	EATON - MOELLER
MPN / Reference	MFD-CP4
Catalog number	0004560921
Category	Text panel
Minimum order	1 Pcs
Document ID	EO-8F7132DCD3
Generated	2026-08-03

Product Overview

Communication module/power supply unit for remote text display, 24 V DC, easy/EC4P/ES4P

CPU Text Module; For remote display; 24 V DC; Cordless; For EASY, EC4P, ES4P

Together with the display and operating unit MFD-80..., the power supply unit / communication module can be used as remote text display for easy500 / easy700 / easy800 / EC4P / ES4P, enclosure degree of protection IP20, without connection cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

Additional Product Information

EL-Nummer (Norway)4560921Communication module/power supply unit for remote text display, 24 V DC, easy/EC4P/ES4PTogether with the display and operating unit MFD-80..., the power supply unit / communication module can be used as remote text display for easy500 / easy700 / easy800 / EC4P / ES4P, enclosure degree of protection IP20, without connection cableDelivery program

Product rangeMulti-function-display MFD-TitanProduct rangeCompact PLCsBasic functionPower supply unit/CPU modulesFunctionAccessoriesAccessoriesRemote text displaySupply voltage24 V DCDescriptionDegree of protection IP20can be combined with display/operating unit MFD-80...

as detachable touch display for easyRelaisDescriptionWithout connection cableDegree of ProtectionIP20Technical data GeneralStandardsEN 61000-6-1/-2/-3/-4, IEC 60068-2-6, IEC 60068-2-27Dimensions (W x H x D)75 x 58 x 36.2

mmWeight0.164 kgMountingFitted onto the fixing shaft of the displayClimatic environmental conditionsOperating ambient temperature-25 to 55, cold as per IEC 60068-2-1, heat as per IEC 60068-2-2 °CCondensationTake appropriate measures to prevent condensationStorage- 40 - 70 °CRelative humidity, non-condensing (IEC/EN 60068-2-30)5 - 95 %Air pressure (operation)795 - 1080 hPaAmbient conditions, mechanicalPollution degree2Protection type (IEC/EN 60529, EN50178, VBG 4)IP20Vibrations (IEC/EN 60068-2-6)Constant amplitude 0.15 mm10 - 57 HzVibrations (IEC/EN 60068-2-6)Constant acceleration 2 g57 - 150 HzMechanical shock resistance (IE...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MFD-CP4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.