

INDUSTRIAL COMPONENT DATA

Eaton 3S 550 IEC 3S550I 9400-43159 EATON ELECTRIC Eaton 3S 550 IEC

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 3S 550 IEC



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 3S 550 IEC
Catalog number	9400-43159
Category	UPS
Minimum order	1 Pcs
Document ID	EO-7A904FF5CA
Generated	2026-08-05

Product Overview

Eaton 3S 550 IEC

Eaton 3S Gen2 UPS IEC, 550 VA, 330 W, Input: C14, Outputs: (4) C13, (4) C13 surge only, USB Communication, Tower

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

General specifications

Product Name Eaton 3S Gen2 UPS Catalog Number 3S550I UPC 743172101815 Product Length/Depth 83.5 mm Product Height 140 mm Product Width 325 mm Product Weight 2.9 kg Compliances CE Marked Certifications IEC/EN 62040-2 CE

EAC

IEC/EN 62040-1 Battery

Battery type Sealed, lead-acid Runtime graph View runtime graph Battery replacement User replaceable Battery quantity 1 Battery management Replaceable batteries, Automatic battery test, deep-discharge protection, cold-start capable Battery rating 12 V / 5 Ah Extended battery capability No Electrical output

Receptacle (4) C13, (4) C13 surge only Voltage 230V Wattage 330W Output power factor 0.6 Output voltage range 184-264 V (adjustable to 161-284 V) Output nominal voltage 230V default (220/230/240V) Voltage distortion output (linear load) - max 0 Feed type 1 Topology Offline VA rating 550 VA Electrical input

Input connection C14 Input nominal voltage 230V default (220/230/240V) Nominal frequency 50/60 Hz Input voltage range 184-264 V (adjustable to 161-284 V) Input frequency range 46-70 Hz Communications

Includes network card No Communication USB port (HID compliant) Ethernet interface No User interface LEDs Potential free switch contact No Expansion slots No Software compatibility Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings) Type of interface USB Environmental Altitude 2000 m Noise level

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 3S 550 IEC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.