

INDUSTRIAL COMPONENT DATA

Eaton 3S 850 DIN 3S850D 9400-A303 EATON ELECTRIC Eaton 3S 850 DIN

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 3S 850 DIN



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 3S 850 DIN
Catalog number	9400-A303
Category	UPS
Minimum order	1 Pcs
Document ID	EO-ED486108AE
Generated	2026-08-03

Product Overview

Eaton 3S 850 DIN

Eaton 3S gen2 DIN UPS, 850 VA, 510 W, Input: Schuko, Outputs: (4) Schuko, (4) Schuko Transient Surge Only, USB Communication, USB Charging (2), Tower

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Single-phase UPS up to 11kVA
--------------	--

Additional Product Information

General Specifications

Product Name Eaton 3S Gen 2 UPS Catalog No. 3S850D Upc 743172101778 Product Length/Depth 83.5 mm Product Height 170 mm Product Width 335 mm Product Weight 4.2 kg Conformance(s) CE marked Certification(s) EAC IEC/EN 62040-2

Ce

IEC/EN 62040-1 Battery

Battery type Sealing, lead-acid Runtime Chart View Runtime Graph Replacing the Battery User-replaceable Number of Batteries 1 Battery Management Replaceable Batteries, Auto Battery Test, Deep Discharge Protection, Cold Start Capability Battery Rating 12 V/9 Ah Extended battery capacity No Electrical Output

Receptacle (4) Schuko, (4) Schuko Single Surges tension 230 V Power in watts 510 W Output Power Factor 0,6 Output Voltage Range 184-264 V (adjustable to 161-284 V) Nominal Output Voltage 230V default (220/230/240V) Type of power supply 1 Topology Offline Nominal Capacity VA 850 VA Electrical Input

Input Connection Protection/Grounding Contact Nominal Input Voltage 230V default (220/230/240V) Nominal Frequency

50/60Hz Input Cable Length 1.5 m Input Voltage Range 184-264 V (adjustable to 161-284 V) Input Frequency Range 46-70 Hz Communications

Includes network card No Communications USB port (HID compatible) Ethernet Interface No User Interface LED Potential-free manoeuvring contact No Expansion Slots No Software Compatibility Eaton UPS Companion (enables safe system shutdown, power consumption measurement, and easy UPS configuration) Interface Type USB Environment Altitude 2,000 m Noise level

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 3S 850 DIN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.