

INDUSTRIAL COMPONENT DATA

Eaton 5PX 1000i RT2U Netpack G2 5PX1000IRTNG2 9210-53051 EATON ELECTRIC Eaton 5PX 1000i RT2U Netpack G2

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 5PX 1000i RT2U Netpack G2



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 5PX 1000i RT2U Netpack G2
Catalog number	9210-53051
Category	UPS
Minimum order	1 Pcs
Document ID	EO-1BC3BC07CB
Generated	2026-08-05

Product Overview

Eaton 5PX 1000i RT2U Netpack G2

Eaton 5PX Gen2 UPS, 1000 VA, 1000 W, Input: C14, Output: (8) C13, Rack/tower, 2U, Network card included

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

General specifications

Product Name Eaton 5PX Gen2 UPS Catalog Number 5PX1000IRTNG2 Model Code Eaton 5PX 1000i RT2U Netpack G2

UPC 743172104878 Product Length/Depth 448 mm Product Height 85.5 mm Product Width 438 mm Product Weight 19.6

kg Compliances IEC/EN 62040-1

IEC/EN 62040-2

IEC/EN 62040-3

RoHS Compliant

REACH

UL 1778

CSA 22.2 Certifications CE

cTUVus

EAC

Cm

UKCA

Ukr

ENERGY STAR certified Battery

Battery type Lead-acid maintenance-free (replaceable) Runtime graph Battery replacement User replaceable Battery quantity 4 Battery management ABM & Temperature compensated charging method (user selectable), Automatic battery test, deep discharge protection, automatic recognition of external battery units Battery rating 12 V / 7 Ah Extended battery capability Yes Electrical output

Receptacle (8) C13 Voltage 230V Wattage 1000 W Output power factor 1 Output voltage range 230 V (+6%/-10%) Output waveform Sine wave Output nominal voltage 230V default (200/208/220/230/240V) Voltage distortion output (linear load) - max 0 Feed type 1 Topology Line-interactive VA rating 1000 VA Electrical input

Input connection C14 Input nominal voltage 230V default (200/208/220/230/240V) Nominal frequency 50-60 Hz Input voltage range 160-294 V (adjustable to 150 V-294 V) Input frequency range 47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40 Hz in low sensitivity mode Communications

Includes network card Yes Communication User interface Multilingual graphical LCD display Potential free switch co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 5PX 1000i RT2U Netpack G2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.