

INDUSTRIAL COMPONENT DATA

Eaton 5PX 3000i RT2U Netpack G2 5PX3000IRTNG2

9210-83122 EATON ELECTRIC Eaton 5PX 3000i RT2U Netpack G2

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 5PX 3000i RT2U Netpack G2



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 5PX 3000i RT2U Netpack G2
Catalog number	9210-83122
Category	UPS
Minimum order	1 Pcs
Document ID	EO-D975F801BF
Generated	2026-08-06

Product Overview

Eaton 5PX 3000i RT2U Netpack G2

Eaton 5PX Gen2 UPS, 3000 VA, 3000 W, Input: C20, Outputs: (8) C13, (2) C19, Rack/Tower, 2U, Network Card Included

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

General specifications

Product name UPS Eaton 5PX Gen2 Catalogue code 5PX3000IRTNG2 Upc 743172104656 Product length/depth 603 mm

Product height 85.5 mm Product width 438 mm Product weight 31.7 kg Conformity IEC/EN 62040-1

IEC/EN 62040-2

IEC/EN 62040-3

RoHS compliant

REACH

UL 1778

CSA 22.2 Certification(s) Ec

cTUVus

EAC

Cm

UKCA

Ukr

KCC

ENERGY STAR certified Model code Eaton 5PX 3000i RT2U Netpack G2 Battery

Battery type Maintenance-free lead-acid (replaceable) Runtime Chart Battery replacement User replaceable Battery

Quantity 6 Battery management ABM and temperature compensation method (user selectable), automatic battery test, full discharge protection, automatic recognition of external battery units Battery rating 12 V/9 Ah Extended battery capacity Yes

Electrical output

Grip (8) C13, (2) C19 tension 230 V Power 3000 W Output Power Factor 1 Output voltage range 230 V (+6%/-10%) Output waveform Sinusoidal Rated Output Voltage 230 V default (200/208/220/230/240 V) Type of power supply 1 Topology

Line-Interactive VA ratings 3000 VA Electrical input

Input connection C20 Nominal input voltage 230 V default (200/208/220/230/240 V) Nominal Frequency 50-60 Hz Input

cable length 1.8 m Input voltage range 160-294 V (adjustable to 150-294 V) Input frequency range 47-70 Hz (50 Hz

system), 56.5-70 Hz (60 Hz system), 40 Hz in low-sensitivity mode Communications

Includes network card Yes Communication User interface Multilingual LCD graphic display Potential-free switching contact

Yes Ex...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 5PX 3000i RT2U Netpack G2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.