

## INDUSTRIAL COMPONENT DATA

# Eaton 5SC 1000i Rack2U 5SC1000IR 9210-53046 EATON ELECTRIC Eaton 5SC 1000i Rack2U

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 5SC 1000i Rack2U



|                 |                        |
|-----------------|------------------------|
| Manufacturer    | EATON - MOELLER        |
| MPN / Reference | Eaton 5SC 1000i Rack2U |
| Catalog number  | 9210-53046             |
| Category        | UPS                    |
| Minimum order   | 1 Pcs                  |
| Document ID     | EO-2D438F7997          |
| Generated       | 2026-08-04             |

## Product Overview

Eaton 5SC 1000i Rack2U

Eaton 5SC UPS, 1000 VA, 700 W, Input: C14, Outputs: (8) C13, Rack, 2U

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Single-phase UPS up to 11kVA

## Additional Product Information

General specifications

Product Name Eaton 5SC UPS Catalog Number 5SC1000IR UPC 743172088321 Product Length/Depth 405 mm Product Height 86.2 mm Product Width 440 mm Product Weight 14.96 kg Compliances CE Marked

TUV Certifications UL 1778

IEC/EN 62040-1

IEC/EN 62040-2

CE

EAC

cTUVus Battery

Battery type Lead-acid maintenance-free (replaceable) Runtime graph View runtime graph Battery replacement User replaceable Battery quantity 2 Battery management ABM or constant voltage charging method (user selectable), automatic battery test, deep discharge protection Battery rating 12 V / 9 Ah Extended battery capability No Electrical output Receptacle (8) C13 Voltage 230V Wattage 700 W Output power factor 0.7 Output voltage range 230 V (+6%/-10%) Output waveform Sine wave Output nominal voltage 230V default (220/230/240V) Feed type 1 Topology Line-interactive VA rating

1000 VA Electrical input

Input connection C14 Input nominal voltage 230V default (220/230/240V) Nominal frequency 50-60 Hz Input voltage range

184-276 V Input frequency range 45-55 Hz (50 Hz system), 55-65 Hz (60 Hz system) Communications

Includes network card No Communication Ethernet interface No User interface LCD Display Potential free switch contact

Yes Expansion slots One slot for optional communication card Software compatibility Eaton Intelligent Power Manager,

Eaton Intelligent Power Protector Type of interface Other Environmental

Altitude 3000 m Noise level

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 5SC 1000i Rack2U with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.