

INDUSTRIAL COMPONENT DATA

Eaton 5SC 3000i RT2U 5SC3000IRT 9210-83117 EATON ELECTRIC Eaton 5SC 3000i Rack/Tower

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 5SC 3000i RT2U



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 5SC 3000i RT2U
Catalog number	9210-83117
Category	UPS
Minimum order	1 Pcs
Document ID	EO-D578286F58
Generated	2026-08-04

Product Overview

Eaton 5SC 3000i Rack/Tower

Eaton 5SC 3000i RT2U

Eaton 5SC UPS, 3000 VA, 2700 W, Input: C20, Outputs: (8) C13, (1) C19, Rack/tower, 2U

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Single-phase UPS up to 11kVA**

Additional Product Information

General specifications

Product Name Eaton 5SC UPS Catalog Number 5SC3000IRT UPC 743172088352 Product Length/Depth 647 mm Product Height 86.2 mm Product Width 441 mm Product Weight 35.3 kg Compliances CE Marked

TUV Certifications IEC/EN 62040-1

UL 1778

IEC/EN 62040-2

CE

EAC

cTUVus Battery

Battery type Lead-acid maintenance-free (replaceable) Runtime graph Battery replacement User replaceable Battery quantity 6 Battery management ABM or constant voltage charging method (user selectable), automatic battery test, deep discharge protection Battery rating 12 V / 9 Ah Extended battery capability No Electrical output

Receptacle (8) C13, (1) C19 Voltage 230V Wattage 2700 W Output power factor 0.9 Output voltage range 230 V

(+6%/-10%) Output waveform Sine wave Output nominal voltage 230V default (220/230/240V) Feed type 1 Topology
Line-interactive VA rating 3000 VA Electrical input
Input connection C20 Input nominal voltage 230V default (220/230/240V) Nominal frequency 50-60 Hz Input cord length
1.8m Input voltage range 184-276 V Input frequency range 45-55 Hz (50 Hz system), 55-65 Hz (60 Hz system)
Communications
Includes network card No Communication Ethernet interface No User interface LCD Display Potential free switch contact
Yes Expansion slots One slot for optional communication card Software compatibility Eaton Intelligent Power Manager,
Eaton Intelligent Power Protector Type of interface Other Environmental
Altitude 3000 m Noise level

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 5SC 3000i RT2U with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.