

INDUSTRIAL COMPONENT DATA

Eaton 9E 3000i Rack2U 9E3000IR 9103-83A23 EATON ELECTRIC Eaton 9E UPS, 3000 VA, 2700 W, Input: C20, Outputs:...

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9E 3000i Rack2U



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9E 3000i Rack2U
Catalog number	9103-83A23
Category	UPS
Minimum order	1 Pcs
Document ID	EO-B10CAF514A
Generated	2026-08-05

Product Overview

Eaton 9E UPS, 3000 VA, 2700 W, Input: C20, Outputs: (6) C13, (1) C19, Rack, 2U

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

General specifications

Product Name Eaton 9E UPS Catalog Number 9E3000IR EAN 3553340710353 Product Length/Depth 608 mm Product Height 86.5 mm Product Width 438 mm Product Weight 31.3 kg Compliances CE Marked

TUV Certifications IEC/EN 62040-1

IEC/EN 62040-2

CE Product specifications

Special features Type UPS Topology Online/Double-conversion Form factor Rack Rack size 2U Construction type 482.6 mm (19 inch) device Color Black VA rating 3000 VA Wattage 2700 W Rack mounting kit Yes Package contents UPS (2) IEC-IEC output cables

USB cable

Rack-mounting kit (rails and brackets)

Safety instructions

Quickstart guide

Internal bypass Yes Hot swap power No Auto shutdown function Yes Primary frequency - max 70 Hz Primary frequency - min 40 Hz Input connection C14 Input cord length 1.8m Input nominal voltage 230V default (220/230/240V) Nominal frequency 50/60 Hz Input frequency range 40-70 Hz Input power factor >.99 Receptacle (6) C13 + (1) C19 Number of Outputs C13 6 Number of Outputs C19 1 Output waveform Sine wave Voltage 230V Output nominal voltage 230V default (220/230/240V) Feed type 1 Voltage type AC Runtime graph Battery management Temperature compensated charging method

Automatic battery test

Deep discharge protection

Battery replacement Replacable batteries Battery rating 12 V / 9 Ah Battery type Sealed, lead-acid Extended battery capability Yes Runtime at half load 10.5 min Communication USB port (HID compliant)

Serial port (RS232)

Mini-terminal block for remote power off

Exp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9E 3000i Rack2U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.