

INDUSTRIAL COMPONENT DATA

Eaton 9PX 1500i RT2U Li-Ion 9PX1500IRT2U-L 9103-LB63163

EATON ELECTRIC Eaton 9PX 1500i RT2U Li-Ion

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9PX 1500i RT2U Li-Ion



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9PX 1500i RT2U Li-Ion
Catalog number	9103-LB63163
Category	UPS
Minimum order	1 Pcs
Document ID	EO-832E2A5A0F
Generated	2026-08-06

Product Overview

Eaton 9PX 1500i RT2U Li-Ion

Eaton 9PX UPS, Lithium, 1500 VA, 1500 W, Input: C14, Outputs: (8) C13, Rack/tower, 2U

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Single-phase UPS up to 11kVA**

Additional Product Information

General specifications

Product Name Eaton 9PX UPS Catalog Number 9PX1500IRT2U-L Model Code Eaton 9PX 1500i RT2U Li-Ion UPC 743172105479 Product Length/Depth 450 mm Product Height 86.5 mm Product Width 440 mm Product Weight 15.8 kg

Warranty 5 year Compliances CE Marked Product specifications

Special features Topology Online/Double-conversion Rack size 2U Construction type 482.6 mm (19 inch) device Color Black/silver VA rating 1500 VA Wattage 1500 W Rack mounting kit Yes Package contents UPS

(2) IEC-IEC output cables

USB cable

Serial cable

(2) brackets for 19' mounting

(2) Rack-mounting kit

(2) Supports for tower mounting

Cable locking system

Safety instructions

Quickstart guide

Internal bypass Yes Hot swap power No Auto shutdown function Yes Primary frequency - max 70 Hz Primary frequency - min 40 Hz Input connection C14 Input nominal voltage 230V default (200/208/220/230/240V) Nominal frequency 50/60 Hz Input frequency range 40-70 Hz Input power factor >.99 Receptacle (8) C13 Number of output connections French standard (Type E) 0 Number of Outputs C13 8 Number of Outputs C19 0 Number of outputs hardwired 0 Num of Outputs PC (SCHUKO) 0 Output waveform Sine wave Voltage 230V Output nominal voltage 230V default (200/208/220/230/240V) Feed type 1 Voltage type AC Runtime graph View runtime graph Battery management Lithium-ion batteries with battery management system
Automatic recognition of external battery units
Battery replacement Hot-swappable internal batteries and extended....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9PX 1500i RT2U Li-Ion with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.