

INDUSTRIAL COMPONENT DATA

Eaton 9PX 2200i RT2U Li-Ion 9PX2200IRT2U-L 9103-LB73949

EATON ELECTRIC Eaton 9PX 2200i RT2U Li-Ion

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9PX 2200i RT2U Li-Ion



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9PX 2200i RT2U Li-Ion
Catalog number	9103-LB73949
Category	UPS
Minimum order	1 Pcs
Document ID	EO-40B286551F
Generated	2026-08-06

Product Overview

Eaton 9PX 2200i RT2U Li-Ion

Eaton 9PX UPS, Lithium, 2200 VA, 2200 W, Input: C20, Outputs: (8) C13, (2) C19, Rack/tower, 2U

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

General specifications

Product Name Eaton 9PX UPS Catalog Number 9PX2200IRT2U-L Model Code Eaton 9PX 2200i RT2U Li-Ion UPC 743172105462 Product Length/Depth 605 mm Product Height 86.5 mm Product Width 440 mm Product Weight 22.1 kg

Compliances CE Marked Battery

Runtime graph Battery management Battery replacement Hot-swappable internal batteries and extended battery modules (EBMs) Battery type Lithium-ion Extended battery capability Yes Electrical output

Receptacle (8) C13, (2) C19 Topology Online/Double-conversion Wattage 2200 W VA rating 2200 VA Output waveform Sine wave Voltage 230V Output power factor 1 Output nominal voltage 230V default (200/208/220/230/240V) Output voltage range 200/208/220/230/240 V +/- 1% Voltage distortion output (linear load) - max 3 Output frequency 50/60 Hz

Feed type 1 Electrical input

Input connection C20 Input cord length 1.8m Input nominal voltage 230V default (200/208/220/230/240V) Input voltage range 176-276 V (100-276 V with derating) Nominal frequency 50/60 Hz Input frequency range 40-70 Hz Input power factor >.99 Communications

Communication USB port (HID compliant)

Serial port (RS232)

Mini terminal block for remote On/Off

Mini-terminal block for remote power off

Mini-terminal block for output relay

Dry contacts (3 outputs, 1 input, optocoupler, DB9)

Expansion slots One slot for optional communication card Ethernet interface No Includes network card No Software compatibility Eaton Intelligent Power Manager, Eaton Intelligent Power Protect...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9PX 2200i RT2U Li-Ion with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.