

INDUSTRIAL COMPONENT DATA

Eaton 9PX 3000i RT2U Li-Ion 9PX3000IRT2U-L 9103-LB83988

EATON ELECTRIC Eaton 9PX 3000i RT2U Li-Ion

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9PX 3000i RT2U Li-Ion



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9PX 3000i RT2U Li-Ion
Catalog number	9103-LB83988
Category	UPS
Minimum order	1 Pcs
Document ID	EO-8B00C49271
Generated	2026-08-06

Product Overview

Eaton 9PX 3000i RT2U Li-Ion

Eaton 9PX UPS Lithium 3000 VA 3000W Input C20 Outputs (8) C13 (2) C19 Rack/Tower 2U

Eaton 9PX Lithium UPS, 3000 VA, 3000 W, Input: C20, Outputs: (8) C13, (2) C19, Rack/tower, 2U

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

General Specifications

Product Name Eaton 9PX UPS Catalog No. 9PX3000IRT2U-L Upc 743172105325 Product Length/Depth 605 mm Product Height 86.5 mm Product Width 440 mm Product Weight 22.8 kg Conformance(s) CE marked Model Code Eaton 9PX 3000i RT2U Li-Ion Electrical output

Receptacle (8) C13, (2) C19 tension 230 V Power in watts 2400 W Output Power Factor 1 Output Voltage Range 200/208/220/230/240 V +/- 1% Output Waveform Sine wave Nominal Output Voltage 230 V default (200/208/220/230/240 V) Voltage Distortion Output (Linear Load) (Max) 3 Type of power supply 1 Topology Double/online conversion Nominal Capacity VA 3,000VA Electrical input

Input Connection C20 Nominal Input Voltage 230 V default (200/208/220/230/240 V) Nominal Frequency 50/60Hz Input Power Factor >99 Input Cable Length 1.8 m Input Voltage Range 176-276 V (100-276 V with power loss) Input Frequency Range 40-70 Hz Communications

Includes network card No Communications Ethernet Interface No User Interface Multi-language LCD graphic display

Potential-free manoeuvring contact Yes Expansion Slots Slot for an optional communication card Software Compatibility

Eaton Smart Power Manager, Eaton Smart Energy Protector Interface Type Other Environmental
Altitude 3,000m Noise level Less than 40 dB at 1 meter Temperature Range 0°C to 40°C (32°F to 104°F) Relative humidity
0-96% non-condensing Additional specifications
Type of construction 482.6 mm (19 inch) device Package Contents UPS
Input Cable
(2) IEC-IEC Output Cables
Cab...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9PX 3000i RT2U Li-Ion with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.