

INDUSTRIAL COMPONENT DATA

Eaton 9PX 8000i 3:1 Power Module 9PX8KIPM31 9105-2213

EATON ELECTRIC Eaton 9PX 8000i 3:1 Power Module

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9PX 8000i 3:1 Power Module



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9PX 8000i 3:1 Power Module
Catalog number	9105-2213
Category	UPS
Minimum order	1 Pcs
Document ID	EO-E49C4A8720
Generated	2026-08-05

Product Overview

Eaton 9PX 8000i 3:1 Power Module

Eaton 9PX 3:1 Power Module, 8 kVA, 7.2 kW, Input: Hardwired, Outputs: Hardwired, Rack/tower, 3U

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Single-phase UPS up to 11kVA**

Additional Product Information

General specifications

Product Name Eaton 9PX UPS Catalog Number 9PX8KIPM31 UPC 743172040121 Product Length/Depth 70 cm Product Height 44 cm Product Width 13 cm Product Weight 23 kg Compliances CE Marked

TUV Certifications IEC/EN 62040-2

IEC/EN 62040-1

CE

EAC Product specifications

Special features Type Power Module Topology Online/Double-conversion Form factor Rack/tower Rack size 3U

Construction type Free standing model Color Black/silver VA rating 8 kVA Wattage 7.2 kW Rack mounting kit No Package contents Power Module

USB cable

Serial cable

(2) Supports for tower mounting

Safety instructions

Quickstart guide

Internal bypass Yes Hot swap power No Auto shutdown function Yes Primary frequency - max 70 Hz Primary frequency - min 40 Hz Input connection Hardwired/fixed connection Input nominal voltage 400V default (380/400/415V) Nominal frequency 50/60 Hz Input frequency range 40-70 Hz Input power factor >.99 Receptacle Hardwired Number of outputs hardwired 1 Output waveform Sine wave Voltage 400V Output nominal voltage 230V default (200/208/220/230/240/250V) Feed type 2 Voltage type AC Runtime graph View runtime graph Battery management ABM & Temperature compensated charging method (user selectable)

Automatic battery test

Deep discharge protection

Automatic recognition of external battery units

Battery replacement No battery Extended battery capability Yes Runtime at half load 0 min Communication USB port (HID compliant)

Serial port (RS232)

Mini terminal block for remote On/Of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9PX 8000i 3:1 Power Module with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.