

INDUSTRIAL COMPONENT DATA

Eaton 9SX 2000i Rack2U 9SX2000IR 9103-73924 EATON

ELECTRIC Eaton 9SX 2000i Rack2U

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9SX 2000i Rack2U



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9SX 2000i Rack2U
Catalog number	9103-73924
Category	UPS
Minimum order	1 Pcs
Document ID	EO-FCAC7A9C60
Generated	2026-08-03

Product Overview

Eaton 9SX 2000i Rack2U

Eaton 9SX UPS, 2000 VA, 1800 W, Input: C14, Outputs: (8) C13, Rack, 2U

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Single-phase UPS up to 11kVA**

Additional Product Information

General specifications

Product Name Eaton 9SX UPS Catalog Number 9SX2000IR UPC 743172090973 Product Length/Depth 608 mm Product Height 86.5 mm Product Width 438 mm Product Weight 26.5 kg Compliances CE Marked

TUV

cULus Listed

CSA 22.2

FCC part 15 Class B

CISPR22 Class B Certifications IEC/EN 62040-1

UL 1778

IEC/EN 62040-2

CE

cULus Listed

EAC Battery

Battery type Sealed, lead-acid Runtime graph Battery replacement Hot-swappable internal batteries and extended battery

modules (EBMs) Battery quantity 6 Battery management Battery rating 12 V / 7 Ah Extended battery capability Yes

Electrical output

Receptacle (8) C13 Voltage 230V Wattage 1800 W Output power factor 0.9 Output voltage range 200/208/220/230/240 V +/- 2% Output waveform Sine wave Output nominal voltage 230V default (200/208/220/230/240V) Voltage distortion output (linear load) - max 3 Feed type 1 Topology Online/Double-conversion VA rating 2000 VA Electrical input Input connection C14 Input nominal voltage 230V default (200/208/220/230/240/250V) Nominal frequency 50/60 Hz Input power factor >.99 Input voltage range 200-276 Vac without derating (up to 140-276 Vac with derating) Input frequency range 40-70 Hz Communications

Includes network card No Communication USB port (HID compliant)

Serial port (RS232)

Mini-terminal block for remote power off

Mini-terminal block for output relay

Dry contacts (2 outputs, 1 input, optocoupler, DB9)

Ethernet interface No User interface Multilingual graphical LCD display Potential free...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9SX 2000i Rack2U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.